

# Avionics

## RGS-2000NG TCAS Test Set

**AEROFLEX**



NextGen TCAS Test Set

The RGS-2000NG TCAS Test Set is an RF signal generator/receiver for testing TCAS (Traffic Alert and Collision Avoidance System) with an option available for testing transponder LRUs. The RGS-2000NG was designed with modern software-driven digital modulation technology and is the RGS-2000 replacement for engineering development, design validation, manufacturing and return-to-service testing.

### Features

- More test capability than any tester in the market, all packed into one box
- Command set emulation of the RGS-2000
- 10.4 inch touch screen LCD display for operator control of all test set capabilities or can be remotely controlled via GPIB or Ethernet
- Simulates 32 dynamic/400 static intruders
- ADS-B squitter encode/decode
- Four port antenna simulation
- Hybrid surveillance
- Six independent transmitters and two receivers
- Data parsing for analysis
- Pulse and frequency measurement
- Software-driven design allows for field updates for adding new features, capability or modifications due to industry changes
- Transponder test option for Modes A, C, S

# TCAS MODE SPECIFICATIONS

---

## TRANSMITTER

### **Frequency**

Range	1025 MHz to 1155 MHz
Resolution	100 KHz
Accuracy	$\pm 10$ KHz

### **Power**

Range	-10 to -90 dBm per element
Resolution	1 dB
Accuracy	$\pm 1$ dB @ 1090 MHz
Port	Top (4 elements) Bottom (4 elements) Any individual element

### **Pulse Modulation**

Accuracy	$\pm 0.05$ uSec
On/Off Ratio	>80 dB
Rise/Fall Time	Normal: <100 nS Slow: 600 nS

External Pulse Modulation

### **Phase Simulation**

Range	0 to 359°
Resolution	1°
Accuracy	Typical < $\pm 1^\circ$ , max $\pm 3^\circ$ (4 port simulation)

### **Range Simulation**

Range	0 to 150 NMI
Resolution	12.5 ft.
Accuracy	$\pm 200$ ft.

### **Velocity Simulation**

Range	0 to 2000 Kts
Resolution	1 Kt/hr

### **Vertical Speed Simulation**

Range	$\pm 32608$ ft./min.
Resolution	64 ft./min.

### **Altitude Simulation**

Range	-1000 to 126,700 ft.
Mode	Gilham and 25 ft.
Resolution	25/100 ft. up to 50,175 ft. 100 ft. above 50,175 ft.

## RECEIVER

### **VSWR**

<1.4

### **Max Input Power**

+57 dBm

### **Internal Ant. Simulation**

### **1030 Rcvr with BPSK Demod**

### **1090 Receiver**

### **Dynamic Range**

40 dB

### **Dual Receiver**

Top/Bottom

### **Power Measurement**

Range	+17 to +57 dBm
Resolution	0.1 dB
Accuracy	$\pm 1$ dB @ 1030 MHz

### **Relative Phase Measurement**

Range	0° to 359°
Resolution	1°
Accuracy	$\pm 4^\circ$

### **Frequency Measurement**

Resolution	1 KHz
Accuracy	$\pm 1$ KHz (using special test mode)

### **Pulse Characteristic Measurement**

Resolution	10 nS
------------	-------

# TRANSPONDER MODE SPECIFICATIONS

---

(Included with RGSNGOPT10 only)

## TRANSMITTER

### **Frequency**

Range	965 MHz to 1095 MHz
Resolution	100 KHz
Accuracy	$\pm 10$ KHz

### **Power**

Range	-10 to -90 dBm
Resolution	1 dB
Accuracy	$\pm 1$ dB @ 1030 MHz
Port	Top and bottom

### **Pulse Modulation**

Accuracy	$\pm 0.05$ uSec
On/Off Ratio	>80 dB
Rise/Fall Time	<100 nS)
External Pulse Modulation	

## RECEIVER

### **VSWR**

<1.4

### **Max Input Power**

+57 dBm

### **1090 Receiver**

### **Dynamic Range**

40 dB

### **Dual Receiver**

Top/Bottom

### **Power Measurement**

Range	+17 to +57 dBm
Resolution	0.1 dB
Accuracy	$\pm 1$ dB @ 1090 MHz

### **Frequency Measurement**

Resolution	10 KHz
------------	--------

### **Pulse Characteristic Measurement**

Resolution	10 nS
------------	-------

## **PHYSICAL CHARACTERISTICS**

---

Power	115/230 VAC, 50/60 Hz
Height	10.5 inches (26.6 cm)
Width	19 inches (48.2 cm)
Depth	16.5 inches (41.9 cm)
Weight	44 lbs. (19.9 kg)

## **FUNCTIONAL CHARACTERISTICS**

---

### **REMOTE INTERFACE**

*Command set emulation of the RGS-2000*

*Ethernet*

*GPIB*

### **INPUTS/OUTPUTS**

*Suppression bus (front/back)*

*ATE lines (front/back)*

*429 Tx/Rx (front/back)*

*2 scope BNC outputs (front/back)*

*LAN (front/back)*

*USB Type B control (front)*

*2 USB Type A (front) for HID/flash drives*

*6 external pulse modulation inputs (back)*

*Top/bottom receiver coupled outputs*

## **ORDERING INFORMATION**

---

<b>Order Number</b>	<b>Description</b>
113956	RGS-2000NG TCAS Test Set <i>(Option RGSNGOPT01 and/or Option RGSNGOPT02 required)</i>
114343	RGSNGOPT01 - Rockwell Collins compatibility option
114344	RGSNGOPT02 - Honeywell compatibility option
114342	RGSNGOPT10 - Transponder test option

**CHINA Beijing**

Tel: [+86] (10) 6539 1166  
Fax: [+86] (10) 6539 1778

**CHINA Shanghai**

Tel: [+86] 21 2028 3588  
Fax: [+86] 21 2028 3558

**CHINA Shenzhen**

Tel: [+86] (755) 3301 9358  
Fax: [+86] (755) 3301 9356

**FINLAND**

Tel: [+358] (9) 2709 5541  
Fax: [+358] (9) 804 2441

**FRANCE**

Tel: [+33] 1 60 79 96 00  
Fax: [+33] 1 60 77 69 22

**GERMANY**

Tel: [+49] 89 99641 0  
Fax: [+49] 89 99641 160

**INDIA**

Tel: [+91] 80 [4] 115 4501  
Fax: [+91] 80 [4] 115 4502

**JAPAN**

Tel: [+81] (3) 3500 5591  
Fax: [+81] (3) 3500 5592

**KOREA**

Tel: [+82] (2) 3424 2719  
Fax: [+82] (2) 3424 8620

**SCANDINAVIA**

Tel: [+45] 9614 0045  
Fax: [+45] 9614 0047

**SINGAPORE**

Tel: [+65] 6873 0991  
Fax: [+65] 6873 0992

**TAIWAN**

Tel: [+886] 3 5500 338  
Fax: [+886] 3 5502 065

**UK Stevenage**

Tel: [+44] (0) 1438 742200  
Fax: [+44] (0) 1438 727601  
Freephone: 0800 282388

**USA**

Tel: [+1] (316) 522 4981  
Fax: [+1] (316) 522 1360  
Toll Free: 800 835 2352



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2013.

[www.aeroflex.com](http://www.aeroflex.com)  
[info-test@eroflex.com](mailto:info-test@eroflex.com)