



ADTS-3250 Air Data Test Set







The ADTS-3250 is a portable, high precision, dual channel pitot static test set designed to calibrate, test and troubleshoot aircraft pitot-static systems and air data instrumentation. The ADTS can be used to test nearly all types of commercial aircraft and meets requirements for RVSM testing. The test set base model is a two-channel system - upgrade to the three-channel model for testing Angle of Attack (AoA).

The 7.0" touchscreen handheld Remote Control Unit can be operated both wirelessly using built-in WiFi direct or hardwired to the test set using the included cable. The intuitive graphical user interface is designed to virtually eliminate the operators learning curve.

Aircraft Pre-Select allows the operator to select pre-loaded aircraft profiles. Once selected, the profile limits the ranges and rates to the aircraft under test. Each aircraft profile can store a virtually unlimited

amount of Test Sequences. These sequences can be programmed to perform semi-automated tests based on job guides or technical orders. This provides improved test consistency while decreasing testing times. Profiles and test sequences can be created and/or edited using the included Profile Builder software.

The remote unit allows the operator the ability to perform aircraft checks and control the test set directly from the cockpit. The WiFi connection provides greater range over Bluetooth systems.

The ADTS can be calibrated automatically using Raptor Scientific ADC Series Air Data Calibrators. Corrections are automated and require no mechanical adjustments. The transducers have been proven to hold their accuracy for a minimum period of one (1) year.







ADTS-3250 Specifications Altitude (Ps) Range -3,000 to 65,000 ft ±3 ft at 0 ft ±7 ft at 30,000 feet **Altitude Accuracy** ±36 ft at 65,000 feet **Altitude Rate** 0 to 20,000 ft/min Accuracy: ±10 ft/min or ±1% setting Altitude Resolution 1 ft, 0.01 mbar, 0.0001 inHg (Ps), 0.01 mmHg **Altitude Units** feet, meters, inHg, mmHg, mbar, hPa, PSIA Airspeed (Pt) Range 0 to 650 knots ±1.50 kts at 50 knots Airspeed Accuracy ±0.10 kts at 550 knots **Airspeed Rate** 0 to 800 kts/min Accuracy: ±10 kts/min or ±1% setting **Airspeed Resolution** 0.1 kt, 0.01 mbar, 0.0001 inHg (Pt), 0.01 mmHg IAS/CAS, kts, Mach, inHg, mmHg, mbar, hPa, PSIA, kph **Airspeed Units Ps2 Differential Function** Range: ±12.00 inHg Accuracy±0.010 inHg Function same as Ps1 **Altitude Function Airspeed Function** Function same as Pt Rate 0 to 20.000 ft/min Display 7.0-inch color LED touchscreen External: Remote, USB / Internal: RS-232, USB Interfaces Calibration Cycle One (1) year Power 90-265 VAC, 50/60 Hz, 1 Phase 25.4 x 20.0 x 14.5 in (62.2 x 50.8 x 36.8 cm) 42 lbs (19.1kg) estimated

Aircraft Pre-Select Feature

Aircraft Pre-Select mode allows the operator to select the aircraft under test. Profiles are pre-loaded at the factory or can be created by the end user. Test Sequences allow the ability to program an unlimited number of individual tests for each stored aircraft profile. These can easily be edited using our free Profile Builder software







