

VIAVI

3920B

Analog and Digital Radio Test Platform

General Specifications

RF Signal Generator	
Frequency	
Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Accuracy	Frequency standard ± 1 count
Output Level	
Range	T/R Port: -130.0 to -30 dBm (-30 dBm max for CW or FM; -35 dBm max for AM modulations; -40 dBm max for complex modulation) GEN Port: -130.0 dBm to +10.0 dBm (+10 dBm max for CW or FM; +5 dBm max for AM modulations; 0 dB max for complex modulation)
Resolution	0.1 dB
Accuracy	1.0 dB for levels > -110 dBm (Typical better than 0.6 dB) 1.5 dB for levels < -110 dBm (Typical better than 1.0 dB)
Spectral Purity	
Residual FM	< 5 Hz (300 Hz to 3 kHz bandwidth)
Residual AM	$< 0.1\%$ RMS (300 Hz to 3 kHz bandwidth)
Harmonics	< -25 dBc (Typically -30 dBc, RF level set at +10 dBm)
Non-Harmonics	< -55 dBc (all freq. except Crossovers) < -35 dBc (at 2nd order crossover frequency) (10 MHz to 1 GHz: Crossover = 1400 MHz - Gen freq.) (1 GHz to 2.7 GHz: Crossover = 3400 MHz - Gen freq.) (Tracking Gen: Crossover = 3410.7 MHz - Gen freq.)
Phase Noise	< -110 dBc / Hz @ 10 kHz offset, RF < 500 MHz < -106 dBc / Hz @ 10 kHz offset, RF < 1000 MHz < -95 dBc / Hz @ 10 kHz offset, RF > 1000 MHz
Modulation	
Selections	OFF, AM, FM, FM50 μ s, FM75 μ s, FM750 μ s, AM USB, AM LSB, IQGEN
Waveforms	Sine, Square, Triangle, Ramp, DCS, DTMF

THD	$< 1\%$ (1 kHz rate, 30 to 70% AM, 6 kHz deviation FM, 300 Hz to 3 kHz BW, Sine)
Internal FM	
Deviation Range	± 0.001 to ± 150 kHz, OFF
Accuracy	3% (From ± 1 kHz to ± 100 kHz deviation, 20 Hz to 15 kHz rate)
Resolution	1 Hz
Deviation Rate	20 Hz to 20 kHz
Internal AM	
Modulation Range	0 to 100%
Accuracy	1% (Modulation from 10% to 90% 20 Hz to 15 kHz rate)
Resolution	0.1%
Rate	20 Hz to 20 kHz
Internal SSB	
Modulation Selection	Upper SideBand (USB) or Lower SideBand (LSB)
Modulation Range	0 to 100%
Resolution	0.1%
Rate	300 Hz to 20 kHz
External AM / FM / SSB	
Audio Inputs	With 1 Vrms, AM / FM / SSB have same characteristics as internal sources, $\pm 10\%$ of indicated setting. (Audio 1 or Audio 2 input from 20 Hz to 15 kHz [300 Hz to 3 kHz SSB] unbalanced). 8 Vrms maximum modulation input level.
Microphone Input	With 50 mVrms, AM / FM / SSB have same characteristics as internal sources, $\pm 10\%$ of indicated setting. (MIC Input from 100 Hz to 15 kHz [300 Hz to 3 kHz SSB]).
Internal IQ Gen	
Sample Rate	< 1.89 Msamples / sec
Size	< 3.8 million samples
Source	File created by IQCreator

RF Receiver	
RF Receiver	
Demod Selections	AM, FM, FM50µs, FM75µs, FM750µs, AM USB, AM LSB
Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Sensitivity	<-100 dBm (10 dB SINAD, FM, 25 kHz, 1 kHz rate, 6 kHz FM Deviation, 300 Hz to 3.4 kHz AF Filter, Pre-amp OFF) <-113 dBm (10 dB SINAD, FM, 25 kHz, 1 kHz rate, 6 kHz FM Deviation, 300 Hz to 3.4 kHz AF Filter, Pre-amp ON)

Demod Output Level

FM	Nominally 1 Vrms (for deviation $\pm 1/4$ of selected BW; 25 kHz BW same output level as 30 kHz BW)
AM	Nominally 2 Vrms (100% AM)

RF Measurements

RF Power Meter (Broadband)

Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 2 MHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 2 MHz)
Level Range	100 mW to 125 W (Usable from 10 mW)
Resolution	4 digits for W or 0.1 dB
Accuracy	10%, 1 digit
Signal	CW, FM, C4FM, 4FSK

RF Power Meter (Inband)

Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (Freq Ext Opt) (Usable from 100 kHz)
Level Range	T/R Port: -60 to +51 dBm Lowest reading is receiver BW dependent (Narrower bandwidths can measure lower levels) ANT Port: -100 to +10 dBm Lowest reading is receiver BW dependent (Narrower bandwidths can measure lower levels)
Resolution	0.1 dB
Accuracy	± 1 dB (Input level above minimum for selected BW [display not yellow], typically better than 0.6 dB)
AM Filter BW	6.25, 8.33, 10, 12.5, 25, and 30 kHz
FM Filter BW	6.25, 10, 12.5, 25, 30, 100, and 300 kHz
Signal	CW, FM, AM, C4FM, 4FSK, OPSK, QAM

RF Counter

Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz, Auto-tune) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz, Auto-tune)
Resolution	1 Hz
Accuracy	Frequency standard ± 1 count
Level Range for Auto-tune	T/R Port: -10 to +50 dBm (Find level is selectable) ANT Port: -60 to +10 dBm (Find level is selectable)
Signal	CW, FM, AM <70% modulation

RF Error Meter	
Range	0 to ± 2.5 MHz from receiver frequency (6 MHz IF BW)
Resolution	1 Hz
Accuracy	Frequency standard ± 1 count
Level Range	T/R Port: -10 to +50 dBm ANT Port: -60 to +10 dBm
Signal	CW, FM, AM <70% modulation

Demodulation Measurements

RF Characteristics

Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Input RF Level	T/R Port: -10 to +50 dBm ANT Port: -80 to +10 dBm

Demod Counter

Range	20 Hz to 20 kHz (1 to 100 kHz FM Deviation, IF BW set appropriately for the received modulation BW) 20 Hz to 10 kHz (30 to 90% AM, IF BW set appropriately for the received modulation BW)
Resolution	0.1 Hz
Accuracy	± 50 ppm (± 10 ppm typical)
Waveform	Sine or Square

FM Deviation Meter

Range	0 to 150 kHz
Resolution	10 Hz
Accuracy	$\pm 3\%$ plus source residual, ± 1 count (1 to 150 kHz FM deviation, IF BW set appropriately for the received modulation BW)
Filter Characteristic Response	0.01 dB (15 kHz low pass audio filter) above 20 Hz
Meter Flatness	0 dB
FM Rate	20 Hz to 20 kHz (IF BW set appropriately for the received modulation BW)

AM Deviation Meter

Range	0 to 100%
Resolution	0.1%
Accuracy	$\pm 3\%$ + source residual, ± 1 count (30 to 90% AM, IF BW set appropriately for the received modulation BW)
AM Rate	20 Hz to 15 kHz (IF BW set appropriately for the received modulation BW)

Audio and Modulation Measurements

Audio Input Characteristics for the following meters	AF Counter, AF Level Meter, SINAD Meter, Distortion Meter, Hum and Noise Meter, Signal-to-Noise Meter
Front Panel Audio Inputs	Audio 1 or Audio 2 (unbalanced, chassis reference) Audio 1 and Audio 2 (balanced, 600 Ω differential input)
Audio Input Impedance (Audio 1 and 2)	Hi-Z (>10 k Ω) - Unbalanced input 600 Ω - Unbalanced Input (8 Vrms MAX input)* 600 Ω - Balanced input (Audio 1 and 2) *Note - 600 Ω unbalanced will auto-switch to Hi-Z @ 8 Vrms

AF Counter	
Range	20 Hz to 20 kHz (usable from 10 Hz)
Resolution	0.1 Hz
Accuracy	±50 ppm max. ±10 ppm typical
Wave shape	Sine or square
Level Range (Audio)	20 mV to 30 Vrms

AF Level Meter	
Range	0 to 30 Vrms
Resolution	Volts: 1 mV (input <1 V) 10 mV (input >1 V) dBr, dBv, dBm: 0.01 dB
Accuracy	5% (Unbalanced, Hi-Z, 300 to 3 kHz, 0.1 to 30 Vrms)
Frequency Range	20 Hz to 20 kHz

SINAD Meter	
Range	0 to 60 dB
Resolution	0.01 dB
Accuracy	±1 dB, ±1 count (SINAD >3 dB, <40 dB, 5 kHz LP AF filter)
Frequency Range	300 Hz to 5 kHz
Level Range (Audio)	0.1 to 30 Vrms

Distortion Meter	
Range	0.0 to 100.0%
Resolution	0.1%
Accuracy	< ±0.5% (Distortion 1 to 10%, 5 kHz LP AF Filter) < ±1.0% (Distortion 10 to 20%, 5 kHz LP AF Filter)
Frequency Range	300 Hz to 5 kHz
Level Range (Audio)	0.1 to 30 Vrms

Hum and Noise	
Range	-100 dB to 0 dB
Resolution	0.01 dB
Accuracy	±1 dB, ±1 count (>-60 dB, <-20 dB)
Signal Frequency	300 Hz to 5 kHz
Audio Input Level	0.1 to 30 Vrms
RF Input Level	T/R Port: -10 to +50 dBm ANT Port: -80 to +10 dBm

Signal-to-Noise Ratio	
Range	-100 to 0 dB
Resolution	0.01 dB
Accuracy	±1 dB, ±1 count (>-60 dB, <-20 dB)
Signal Frequency	300 Hz to 5 kHz
Audio Input Level	0.1 to 30 Vrms
RF Input Level	T/R Port: -10 to +50 dBm ANT Port: -80 to +10 dBm

Modes				
Mode	Stimulus	Stimulus Port	Measurement Input	Measurement Port
1	RF Generator	TR / Gen	AF Input	Audio In 1 or 2
2	AF Generator	Fctn Gen Out	RF Receiver	TR / Antenna

Audio Filters (Characteristic Response)				
Filter	Type	Ripple	-1 dB	-60 dB
None	No Filter			
300 Hz	Low-Pass	<0.23 dB, above 20 Hz	330 Hz	590 Hz
5 kHz	Low-Pass	<0.02 dB, above 20 Hz	5.5 kHz	6.7 kHz
15 kHz	Low-Pass	<0.01 dB, above 20 Hz	16.1 kHz	17.8 kHz
20 kHz	Low-Pass	<0.01 dB, above 20 Hz	20.4 kHz	21 kHz
0.3 to 3.4 kHz	Band-Pass	<1.7 dB	320 Hz / 3.8 kHz	60 Hz / 5.2 kHz
0.3 to 5 kHz	Band-Pass	<1.7 dB	320 Hz / 5.2 kHz	60 Hz / 9.6 kHz
0.3 to 15 kHz	Band-Pass	<1.7 dB	320 Hz / 16.1 kHz	60 Hz / 19.9 kHz
0.3 to 20 kHz	Band-Pass	<1.7 dB	200 Hz / 20.4 kHz	60 Hz / 21 kHz
PSOPH C-MSG	Band-Pass	Per C-MSG Spec	Per C-MSG Spec	Per C-MSG Spec
PSOPH CCITT	Band-Pass	Per CCITT Spec	Per CCITT Spec	Per CCITT Spec
300 Hz	High-Pass	<1.7 dB	320 Hz	60 Hz

Audio Function Generator(s)	
Wave Shape	Sine, Square, Triangle, Ramp, Digital Coded Squelch, DTMF

Frequency	
Range	Sine: 20 Hz to 40 kHz (usable from 1 Hz to 40 kHz) Square, Triangle and Ramp: 20 Hz to 4 kHz (usable 1 Hz to 40 kHz)
Resolution	0.1 Hz
Accuracy	±50 ppm, ±10 ppm typical

Level	
Range	1 mV to 5 V RMS into a 10 kΩ load
Resolution	0.1 mV
Accuracy	±1% of setting (10 kΩ load)
Impedance	<10 Ω
Spectral Purity	<0.5% (1 kHz, 5 Vrms, 80 kHz BW, 10 kΩ load, Sine) <1.0% (Typical, 20 Hz to 20 kHz, 100 mV to 5 Vrms, 80 kHz BW, 10 kΩ load, Sine)

Oscilloscope	
Display	
Traces	2
Trace Types	Live, captured, accumulated
Markers	2
Marker Functions	Time with amplitude, deviation or % depth Delta marker (including 1/Δ t, e.g. Hz)
Vertical	
3 dB Bandwidth	16 MHz
Frequency Range	DC to 4 MHz (40 MS / s sampling rate)
Input Range	0 to 100 Vpeak Max, Category II
Scales	2 mV to 20 V / division in a 1, 2, 5 sequence (8 [h] x 10 [w] graticule display)
Accuracy	5% of full scale (DC to 1 MHz) 10% of full scale (1 to 4 MHz)
Resolution	Better than 1% of full scale
Coupling	DC, AC, GND
Horizontal	
Sweep Factors	1 μSec to 1 Sec / division in a 1, 2, 5 sequence
Accuracy	>1.5% of full scale
Resolution	>1% of full scale
Input Impedance	1 MΩ, 20 pF
Trigger	
Trigger Source	Trace A, Trace B, EXT, (or Trace C with no CH1 or CH2 Input)
Trigger Edge	Rising / falling
Trigger Mode	Auto / normal Continuous / single shot
External Trigger Level	Hi-Z BNC input on the rear panel of the unit Adjustable from -5 to +5 V
Digital Multimeter	
AC / DC Voltmeter	
Full Scale Range	200 mV, 2 V, 20 V, 200 V, 2000 V, Auto (150 VAC RMS or VDC MAX input Category II)
Resolution	3-½ digits (2000 counts)
Accuracy	DC ±1% Full Scale ±1 count AC ±5% Full Scale ±1 count
AC Volts Frequency Range	50 Hz to 10 kHz
AC / DC Ammeter	
Full Scale Range	200 mA, 2 A, 20 A, Auto (20 A range uses optional shunt connected to Voltmeter)
Maximum Open Circuit Input Voltage	30 Vrms referenced to common on earth ground, Category I
Resolution	3-½ digits (2000 counts)
Accuracy	±5% Full Scale ±1 count
AC Volts Frequency Range	50 Hz to 10 kHz

Ohmmeter	
Full Scale Range	200 ohms, 2 kohms, 20 kohms, 200 kohms, 2 Mohms, 20 Mohms, Auto
Maximum Open Circuit Input Voltage	30 Vrms referenced to common or earth ground, Category I
Resolution	3-½ digits (2000 counts)
Accuracy	±5% Full Scale ±1 count
External Current Shunt (Optional)	
Rating (Category II)	10 amps, 100 mV 20 amps - ON 1 minute, OFF 4 minutes
Accuracy (18° to 28° C)	DC to 10 kHz: ±0.25%
Temperature Coefficient	0.005% / ° C
RF Spectrum Analyzer	
Frequency	
Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392xOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Accuracy	Same as frequency standard
Span	
Mode	Start / Stop, Center / Span, and Zero Span
Range	Selection list is 2 kHz to Full Span in a 1, 2, 5 sequence, plus Zero Span (Span may be entered numerically down to 1 Hz resolution)
Display Accuracy	Span Accuracy + Frequency Accuracy + 50% of RBW
Span Accuracy	±1% of span width
Marker Accuracy	±1% of span width
Level	
Ref Level Range	T/R Port: -50 to +50 dBm ANT Port: -90 to +10 dBm
Vertical Scales	1, 2, 5, 10 dB / division
Reference Level Resolution	0.1 dB
Ref Level Units	dBm
Dynamic Range	70 dB (Antenna, no attenuation, Ref Level -30 dBm, 30 kHz RBW)
Bandwidth Switching Error	±1 dB (After Normalize)
Log Linearity	±1 dB (RBW: 3 kHz, 30 kHz, 60 kHz, 300 kHz, 6 MHz) ±1 dB (300 Hz RBW typical)
Accuracy	±1 dB (Input signal -10 dB from Ref Level, Normalized, preamp off)
Attenuator Selections	0 to 50 dB of attenuation, controlled by changing the Ref Level
3rd Order Intermodulation	-60 dBc (Input Level of -30 dBm, Ref Level at -20 dBm)
Harmonic Spurious	-55 dBc (Input Level of -30 dBm, Ref Level at -20 dBm)

Level - Continued	
Non-Harmonic Spurious	-60 dBc (Input Level of -30 dBm, Ref Level at -20 dBm)
Displayed Average Noise Level (DANL)	-125 dBm (Typical, 300 Hz RBW, ANT Port terminated, 20 sweep average)
Resolution Bandwidth	
RBW Selections	300 Hz, 3 kHz, 30 kHz, 60 kHz, 300 kHz, 6 MHz
RBW 60 dB / 3 Filter Shape	>10:1
Selectivity - Filter Shape	60 dB / 3 dB ratio better than 10:1
Accuracy	±10% of RBW for 3 kHz, 30 kHz, 60 kHz, 300 kHz -10% / +25% of RBW for 6 MHz ±20% of RBW for 300 Hz
Bandwidth Switching Error	±1 dB
Video Bandwidth	
Range	10 Hz to 1 MHz in a 1, 3, 10 sequence, plus NONE
Sweep	
Frequency Sweep Time	100 mS to 100 S in a 1, 2, 5 sequence
Zero Span Sweep Time	50 mS to 100 S in a 1, 2, 5 sequence
Sweep Trigger Source	Internal and External
Trigger Modes	Continuous (repeat), single (single-shot)
Function / Feature	
Display Modes	Live, average, max hold
Averages	1 to 100
Markers	
Track	Frequencies (or time) and amplitudes
Number of Markers	8
Marker Functions	Marker to Peak Marker to Next Right / Left Marker to Minimum Marker to Ref Level Marker to Center Frequency Marker sets Span Marker sets Vertical Scale (Zero Span only)
Tracking Generator (Optional)	
Tracking Generator Output	Refer to RF Signal Generator section for: -Frequency range and accuracy -Output level range, resolution, and accuracy - Spectral purity
Span and Sweep Time	Same as Spectrum Analyzer
Tracking Generator Controls	Output port selection, RF level, Reference cal
Harmonics and Spurious (Optional)	
Harmonic Level	
Range	0 to -60 dBc
Resolution	0.1
Accuracy	Same as RF Spectrum Analyzer

Spurious Level	
Range	0 to -60 dBc
Resolution	0.1
Accuracy	Same as RF Spectrum Analyzer
Audio Spectrum Analyzer (Optional)	
Frequency	
Range	Start and Stop Frequency - 0 Hz to 24,000 Hz
Resolution	1 Hz
Accuracy	±50 ppm (±10 ppm Typical)
Span	2 kHz min to 24 kHz max
Level	
Vertical Scales	1, 2, 5, 10, 20 dB per division
Reference Level	0 dB Full Scale (dBr)
Dynamic Range	Greater than 120 dB
Accuracy	±1 dB from 300 Hz to 15 kHz
Markers	
Number of Markers	2
Frequency Standard I/O	
Internal Frequency Standard Output	
Frequency	10 MHz (nominal)
Output Level	1 Vpp (nominal) into 50 Ω
Temperature Stability (0 to 50° C)	±0.01 ppm
Aging Rate	±0.1 ppm / year after 1 month continuous use
Warm Up Time	Less than 5 min. to ±0.02 ppm
External Frequency Input	
Frequency	10 MHz
Input Level	1 to 5 Vpp for sine waves 3.3 / 5 V TTL for square waves
Connector	BNC socket (10 k Ω Input / 50 Ω Output)
Input / Output Connectors	
ANT (RF Input)	
Connector Type	TNC
Function	Receiver input
Impedance	50 Ω (nominal)
VSWR (with Attenuation <10 dB)	Better than 1.44:1 (RF freq. <1.05 GHz) Better than 1.58:1 (RF freq. >1.05 GHz to <2.7 GHz)
Input Protection	10 W with warning above +17 dBm (Remove power immediately when alarm sounds)
Gen (RF Output)	
Connector Type	TNC
Function	Generator high-level output
Impedance	50 Ω (nominal)
VSWR (with level <0 dBm)	Better than 1.7:1 (RF freq. <1.05 GHz) Better than 1.9:1 (RF freq. >1.05 GHz to <2.7 GHz)
Input Protection	10 W with warning above +23 dBm (Remove power immediately when alarm sounds)

T/R (RF Input / Output)	
Connector Type	Type N
Function	RF power input, generator low-level output
Impedance	50 Ω (nominal)
VSWR	Better than 1.2:1 (RF freq. <1.05 GHz) Better than 1.3:1 (RF freq. >1.05 GHz to <2.7 GHz)
Input Protection	200 W with warning above 135 W or power termination temp >100° C. Recommended max of 30 s ON and minimum of 2 min OFF for power levels above 50 W. (Remove power immediately when alarm sounds)
GPIB	
Connector Type	24 pin IEEE
Function	IEEE-488, 1-1997
Ethernet	
Connector Type	8 position, RF-45 100 / 10 Mbit / s
Function	10 / 100 Base-T network connection
RS-232	
Connector Type	9-pin, D-sub, Male
Baud Rates	300, 600, 1200, 2400, 4800, 9600, 19.2k, 38.4k, 57.6k, 115.2k
Stop Bits	1 or 2
Parity	Odd, even, none
Video	
Connector Type	15-pin, D-sub, VGA
Function	VGA for external monitor
IF Output	
Connector Type	BNC
Function	10.7 MHz Receiver IF
Output Level	Proportional to Receive Signal Level
Mic / Accessory	
Connector Type	8 position, female DIN
Function	Microphone connection, modulation input, demod output, PTT operation
Parallel Port	
Connector Type	25 position, female D-sub
Function	Printer interface
USB	
Connector Type	Twin USB standard connection (rear panel) Single USB standard connection (front panel)
Function	IEEE-488, 1-1997
Test Port	
Connector Type	15 position, female 3 tier D-sub
Function	Programmable I/O and voltage output (optional interface)
Auxiliary IF Input	
Connector Type	High-density dual inline
Function	External digital receiver input (optional interface)
AC Power Requirements	
Mains Supply Voltage	110 V to 220 VAC \pm 10%

Mains Supply Frequency	50 Hz to 60 Hz \pm 5%
Power Consumption	Nominally 120 W (200 W Max)
Fuse Requirements	3 A, 250 V, Type F

Environmental / Safety	
Operating Temperature	0 to 50° C (Tested in accordance with MIL-PRF-28800F Class 3)
Warm-up Time	15 minutes
Storage Temperature	-40 to +71° C (Tested in accordance with MIL-PRF-28800F Class 3)
Relative Humidity	80% up to 31° C decreasingly linearly to 50% at 40° C (Tested in accordance with MIL-PRF-28800F Class 3)
Altitude	4,000 m (13,123 ft) (MIL-PRF-28800F Class 3)
Shock and Vibrations	30 G Shock (functional shock) 5-500 Hz random vibrations (Tested in accordance with MIL-PRF-28800F Class 3)
Use	Pollution degree 2
EMC	EN 61329, Class 2
Reliability	>8,000 hour calculated MTBF (MIL-HDBK-217F, notice 2)
Safety Standards	UL 6101B-1 EN 61010-1 CSA C22.2 No.61010-1

Dimensions and Weight	
Height	7.75" (19.7 cm)
Width	14" (35.6 cm)
Depth	18.5" (47.0 cm)
Weight	36.8 lbs (16.5 kg)

General Characteristics	
LCD Display Screen Size	6.4" diagonal 162.6 mm diagonal
Active Area	5.1" (h) x 3.8" (v) 129.6 mm (h) x 97.44 mm (v)
Resolution	640 x 480 pixels
Disk Storage	Internal 30 GByte hard disk available for user storage

P25 (Optional System)

RF Signal Generator	
Frequency	
Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Accuracy	Frequency standard \pm 1 count
Output Level	
Range	T/R Port: -138.0 to -30.0 dBm for C4FM and H-CPM modulations (-40.0 for all other modulations) GEN Port: -130.0 to +10.0 dBm for C4FM and H-CPM modulations (+0.0 dBm for all other modulations)

Resolution	0.1 dB
Accuracy	1.0 dB for levels >-110 dBm (Typical better than 0.6 dB) 1.5 dB for levels <-110 (Typical better than ±1.0 dB)
Modulation	C4FM, CQPSK, LSM
Test Patterns	STD 1011, STD CAL, STD SILENCE, STD INTFR, STD BUSY, STD IDLE, STD 511 (0.153), STORED SPCH, VOICE, 1011, SILENCE

RF Receiver

Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Level Range	T/R Port: -10 to +50 dBm ANT Port: -60.0 to +10 dBm (with preamp -63)

P25 Measurements

Modulation Fidelity

Range	0 to 20%
Resolution	0.1%
Accuracy	<5.0% of reading (2.5 to 10%)

Symbol Deviation

Range	1500 Hz to 2100 Hz
Resolution	0.1 Hz
Accuracy	±10 Hz (1620 to 1980 Hz)

Symbol Clock Error

Range	±100 mHz
Resolution	0.01 mHz
Accuracy	1 ppm (±4.8 mHz)

Frequency Error

Range	±4000 Hz
Resolution	0.01 Hz
Accuracy	Frequency Standard ±1 count

UUT TX / RX Bit Error Rate

Range	0 to 20%
Resolution	0.1%

Signal Power

Range	T/R Port: -60 to +51 dBm ANT Port: -100 to +10 dBm
Resolution	0.1 dB
Accuracy	±1 dB (typically better than ±0.6 dB)

Error Vector Magnitude

Range	0 to 20%
Resolution	0.01%

Carrier Feedthrough

Range	0 to -80.00 dB
Resolution	0.01 dB

Graphical Displays

Modulation Fidelity Displays

Constellation	Line graph of the deviation at the symbol point.
Distribution	Graph of the statistical distribution of the deviation at the symbol point. This is a graph of the deviation at the symbol point versus the percentage of occurrence of that deviation.
Eye Diagram	Graph of the demodulated signal versus time, synchronized with the symbol points. The number of symbol periods is selectable. Range is 2 to 16.
Trajectory	Graph of the demodulated signal in the complex domain. This graph shows the Inphase versus the Quadrature phase of the demodulated C4FM, CQPSK, or LSM signal.

Protocol

Data Link

Header	MFID, ALG, KEY, TGID, MI
Voice Frame	Frame #, NAC, DUID, KEY, ALG, MI, RAW, LCO, Protect, SF, EMG, LSD, STS, STS 2
Conventional Mode Simulation	NAC, Call Type, TGID, UID, Alg ID, Key ID

Phase I Trunking Simulation

System Plans	Basic 800, Basic UHF, Basic VHF, Basic 700, plus multiple user defined
User Defined Fields	System ID, WACN, RFSS ID, Site ID, Announcement Group Address, Local Registration Area, Service Class, Active Network, Local / Global Affiliation, Group Affiliation, Registration, WGID Mapping, WUID mapping, Protected 16 Channel IDs with Base Frequency, Bandwidth, TX Offset, Channel Spacing
Trunking Control	Base Simulation sets System Plan, Implicit / Explicit mode, Control Channel ID / NUM / Frequency, Control Channel power level, Control Channel modulation, Traffic Channel ID / NUM / Frequency, Traffic Channel power level, Traffic Channel modulation
Simulator	Call Type, TGID, UID, Alg ID, Key ID
Encryption	Supports DES Encryption (AES available with restrictions)

DMR (Optional System)

RF Signal Generator

Frequency

Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Accuracy	Frequency standard ±1 count

Output Level

Range	T/R Port: -130.0 to -40.0 dBm GEN Port: -130.0 to +0.0 dBm
Resolution	0.1 dB
Accuracy	1.0 dB for levels >-110 dBm (Typical better than 0.6 dB) 1.5 dB for levels <-110 (Typical better than 1.0 db)

Modulation	4-FSK
Test Patterns	STD IB 1031, STD IB CAL, STD IB 511 (0.153), STD OB TSYNC (Repeater IDLE pattern)
RF Receiver	
Frequency Range	
Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Level Range	T/R Port: -10 to +50 dBm ANT Port: -60.0 to +10 dBm (with preamp -63)
DMR Measurements	
FSK Error	
Range	0 to 20%
Resolution	0.01%
Accuracy	<5% of reading (2.5 to 10%)
Symbol Deviation	
Range	1500 Hz to 2350 Hz
Resolution	0.1 Hz
Accuracy	±10 Hz (1745 to 2140 Hz)
Symbol Clock Error	
Range	±1000 mHz
Resolution	0.01 mHz
Accuracy	1 ppm (-48 to +48 mHz)
Frequency Error	
Range	±4000 Hz
Resolution	0.01 Hz
Accuracy	Frequency Standard ±1 count
Magnitude Error	
Range	0 to 5%
Resolution	0.01%
Accuracy	<10% of reading (0 to 2%)
UUT TX / RX Bit Error Rate	
Range	0 to 20%
Resolution	0.1%
Signal Power / Slot Power	
Range	T/R Port: -60 to +51 dBm ANT Port: -100 to +10 dBm
Resolution	0.1 dB
Accuracy	±1 dB (typically better than ±0.6 dB)
Protocol	
Decode	Color Code, Call ID, Unit ID
Accuracy	Color Code, Call ID

dPMR (Optional System)

RF Signal Generator	
Frequency	

Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Accuracy	Frequency standard ±1 count
Output Level	
Range	T/R Port: -138.0 to -30.0 dBm for 4FSK GEN Port: -130.0 to +10.0 dBm for 4FSK
Resolution	0.1 dB
Accuracy	1.0 dB for levels >-110 dBm (Typical better than 0.6 dB) 1.5 dB for levels <-110 (Typical better than 1.0 dB)
Modulation	4FSK
Test Patterns	STD 511 (0.153)

RF Receiver	
Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1 Hz
Level Range	T/R Port: -10 to +50 dBm ANT Port: -60.0 to +10 dBm (with preamp -63)

dPMR Measurements	
FSK Error	
Range	0 to 20%
Resolution	0.01%
Accuracy	<5.0% of reading (2.5 to 10%)
Symbol Deviation Meter	
Range	875 Hz to 1225 Hz
Resolution	0.1 Hz
Accuracy	±10 Hz (945 to 1155 Hz)
Symbol Clock Error Meter	
Range	±1000 mHz
Resolution	0.01 mHz
Accuracy	1 ppm (-24 to +24 mHz)

Frequency Error	
Range	±4000 Hz
Resolution	0.01 Hz
Accuracy	Frequency Standard ±1 count

UUT TX BER Meter	
Range	0 to 20%
Resolution	0.1%

Signal Power Meter	
Range	T/R Port: -60 to +51 dBm ANT Port: -100 to +10 dBm
Resolution	0.1 dB
Accuracy	±1 dB (±0.6 dB typical)

Graphical Displays	
<i>Modulation & Power Analysis</i>	
Constellation	Line graph of the deviation at the symbol point.
Distribution	Graph of the statistical distribution of the deviation at the symbol point. This is a graph of the deviation at the symbol point versus the percentage of occurrence of that deviation.
Eye Diagram	Graph of the demodulated signal versus time, synchronized with the symbol points. The number of symbol periods is selectable. Range is 2 to 16.
Power Over Time	Displays the power measurement of the received signal over a specified period of time; indicating the transmitter's stability

TETRA (Optional System)

RF Signal Generator	
<i>Frequency</i>	
Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Resolution	1.0 Hz
Accuracy	Frequency Standard ± 1 count
<i>Output Level</i>	
Range	T/R Port: -130.0 to -40.0 dBm GEN Port: -130.0 to 0 dBm
Resolution	0.1 dB
Accuracy	1.0 dB for levels > -110 dBm (Typical better than 0.6 dB) 1.5 dB for levels < -110 (Typical better than 1.0 dB)
<i>Modulation</i>	
Type	$\pi/4$ DQPSK, 18 ksymbols / sec, TETRA filter (RRC with <0.35)
Accuracy	<3% RMS <6% peak
Residual Carrier Power	<-35 dBc
<i>Test Signals</i>	
TETRA MS	Main Control Channel (MCCH) Traffic Channel (TCH / S) containing silence or 1 kHz tone or talk-back, Fast Associated Control Channel (FACCH)
TETRA MS T1	T1 test signals (in accordance with ETSI EN 300 394-1) T1 type 7 (TCH / 7.2), T1 type 2 (SCH / F), T1 type 3 (BSCH + SCH / HD), T1 type 4 (TCH / 2.4), T1 type 15 (TCH / S), T1 type 17 (TCH / 4.8)
TETRA BS T1	T1 test signals (in accordance with ETSI EN 300 394-1) T1 type 7 (TCH / 7.2), T1 type 8 (SCH / F), T1 type 9 (STCH + STCH UL), T1 type 10 (TCH / 2.4), 18 Frame PRBS. Framed PRBS, Unframed PRBS
TETRA DM	Traffic Channel (TCH / S) containing silence or 1 kHz tone or talk-back

RF Receiver	
Frequency Range	10 MHz to 1.05 GHz (Standard) (Usable from 100 kHz) 10 MHz to 2.7 GHz (392XOPT058) (Usable from 100 kHz)
Level Range	T/R Port: -40 dBm to +40 dBm ANT Port: -80 dBm to 0 dBm
Burst Types	MS: Control Burst (CB), Normal Uplink Burst (NUB) BS: Normal Downlink Burst (TS1+2, TS1, and TS2) Synchronization Burst, PRBS with no training sequence

TETRA Measurements	
POWER	Average power across the useful part of the burst measured at the symbol points through a TETRA filter
Resolution	0.1 dB
Accuracy	± 1.0 dB (± 0.6 dB typical)
MODULATION ACCURACY	Modulation accuracy measures the displacement of symbol points from their ideal position
Range	20.0% RMS vector error 40.0% Peak vector error 20.0% Residual carrier
Resolution	0.1%
Accuracy	$\pm 0.5\%$ at 10% error
BURST TIMING ERROR	Timing error relative to downlink results available for avg max, min and worst case for a sample of up to 250 bursts
Range	± 510.0 symbols
Resolution	0.01
Accuracy	± 0.05 symbols
Timing offset range	± 999.99 symbols

Frequency Error	
Range	± 500.0 Hz
Resolution	0.1 Hz
Accuracy	± 15 Hz +frequency standard accuracy
BER Testing (TETRA MS T1 mode)	BER, MER, and PUEM
BER Testing (TETRA MS mode)	BER, RBER, and MER
BER Testing (TETRA BS T1 mode)	BER, MER, and PUEM

Graphical Displays	
<i>Modulation & Power Analysis</i>	
Constellation	Line graph of the deviation at the symbol point.
Distribution	Graph of the statistical distribution of the deviation at the symbol point. This is a graph of the deviation at the symbol point versus the percentage of occurrence of that deviation.

Eye Diagram	Graph of the demodulated signal versus time, synchronized with the symbol points. The number of symbol periods is selectable. Range is 2 to 16.
Power Over Time	Displays the power measurement of the received signal over a specified period of time; indicating the transmitter's stability
Graphical Displays	
POWER PROFILE DISPLAY	Display of power versus time for a complete burst or ramp up / ramp down intervals measured at the symbol points and displayed relative to a TETRA mask (TETRA limits are user defined) with pass / fail indication. Measured through a TETRA filter referenced (0 dB) to average power.
Dynamic Range	70 dB
Vertical Scale	2 dB / div or 0.1 dB / div in 1, 2, 5 steps
Accuracy	±1.0 dB (±0.6 dB typical) at symbol points for levels greater than -10 dB
CONSTELLATION DISPLAY	Polar display of amplitude versus phase at the symbol point measured over all symbols (SN0 ~ SN max) through a TETRA filter. Also available as a rotated constellation display where all symbol point values are mapped to a single constellation point.
PHASE TRAJECTORY DISPLAY	Polar display of amplitude versus phase continuously measured over the duration (SN0 ~ SN max) through a TETRA filter.
Graphical Displays - Continued	
VECTOR ANALYSIS DISPLAY	Vector error (%), magnitude error (%), and phase error (degrees) measured at symbol points (SN0 ~ SN max) through a TETRA filter.
Vertical Scaling	Vector error 0.1% / div to 20% / div in 1, 2, 5 steps Phase error ±0.1° / div to ±20° / div in 1, 2, 5 steps Magnitude error ±1.0% / div to ±20% / div in 1, 2, 5 steps
TETRA Channel Plans and Signaling	
Channel Plans	TETRA 380-400 (0 Hz or 12.5 kHz offset) TETRA 410-430 (0 Hz, 6.25 kHz, or 12.5 kHz offset) TETRA 450-470 (0 Hz or 12.5 kHz offset) TETRA 805-870 (0 Hz or 12.5 kHz offset) TETRA 870-921 (0 Hz or 12.5 kHz offset) No plan and user defined
System Identify	Mobile County Code, MCC Mobile Network Code, MNC Base Color Code, BCC Location Area Code, LA

Signaling Functions	Mobile parameter control for SSI, GSSI, power class, receiver class Registration, test mode registration and de-registration Private (individual) call, group call, phone call, emergency call, user defined call (mobile terminated) Call timer and trunking type selection Cell re-selection (requires two test sets and a power splitter) Short data service Status message and SDS types 1 to 4 call control (simplex calls) Power control and Frequency control Frequency handoff RF loopback control (TT) Display of mobile information Demodulated and channel decoded data Protocol history display Talk back, silence and test tone (1 kHz digitally encoded)
---------------------	---

Ordering Information

Versions and Options

Order Number	Description
91164	3920B Analog and Digital Radio Test Platform
Standard Accessories	
Front / Rear Cover	
Adapter (BNC-F to TNC-M x2)	
Adapter (N-M to BNC-F)	
AC Line Cord	
Antenna (BNC) (450 MHz)	
Antenna (BNC) (800 MHz)	
Antenna (BNC) (150 MHz)	
112265	3920B Digital Radio Test Set FAA
88459	3920N Digital Radio Test Set
89871	3920N Test Accessory Kit
Options	
83352	390XOPT051 Site Monitoring Applications
83353	390XOPT054 IQ Gen Modulation
83354	390XOPT055 Audio Analyzer
83368	390XOPT210 Analog Simulcast Option (Requires Opt055)
83390	392XOPT058 2.7 GHz Frequency Range Extension Option
83356	390XOPT060 Harmonics & Spurious Measurements
83357	390XOPT061 Tracking Generator
83358	390XOPT064 Analog Duplex Power Between Markers

92573	390XOPT067 POCSAG
83359	390XOPT110 TETRA MS (Mobile Station Testing)
83362	390XOPT114 TETRA Energy Economy Mode (Requires Opt110)
83360	390XOPT111 TETRA BS (Base Station Testing)
83361	390XOPT112 TETRA DM (Direct Mode Testing)
83363	390XOPT200 P25 Conventional Operation (with DES OFB Type III)
83364	390XOPT201 P25 Trunking Operation VHF / UHF / 700 / 800 MHz (Requires Opt200)
83369	390XOPT212 Explicit Mode Trunking (UHF / VHF only) (Requires Opt201)
83370	390XOPT213 Unit to Unit Call (Requires Opt212)
83371	390XOPT214 Adjacent Channel Broadcast Message (Requires Opt201)
83372	390XOPT215 Secondary Control Channel Broadcast Message (Requires Opt201)
84412	390XOPT260 P25 Performance Test Triggers (Requires Opt200 and Opt201)
83365	390XOPT204 LSM Generate and Receive / Analysis (Requires Opt200)
83366	390XOPT206 P25 Control Channel Logger Option (Requires Opt200)
82566	390XOPT230 Off Air Monitor Software for P25 Message Logging - Protocol Analysis Tool (Requires Opt206)
83367	390XOPT207 SMARTNET / SmartZone Option (Requires Opt200)
62377	390XOPT209 KVL 3000 & 4000 Keyloader Option (Requires Opt200)
90532	390XOPT220 Phase 2 Two-Slot Time Division Multiple Access Physical Layer (Requires Opt200)
67444	390XOPT240 P25 AES Encryption (Requires Opt200)
83378	390XOPT250 Occupied Bandwidth for P25 (Requires Opt200)
83383	390XOPT400 DMR (MOTOTRBO) ETSI 102-361
84413	390XOPT402 DMR XML Channel Logger Option (Requires Opt400)
84414	390XOPT420 dPMR - ETSI 102-658
90533	390XOPT422 dPMR Control Channel Logger Option (Requires Opt420)
84416	390XOPT440 NXDN
104218	390XOPT442 NXDN XML Channel Logger (Requires Opt440)
84418	390XOPT460 ARIB T98
140219	390XOPT462 ARIB T98 Channel Logger (Requires Opt460)

Auto-Test and Alignments	
Analog Radios	
83355	390XOPT059 Auto-Test II Environment for Analog Radio Systems
83387	390XOPT603 TIA / EIA-603 FM Land Mobile Test Software (Requires Opt059)
138575	390XOPT624 Collins Aerospace 721S Blade Auto-Test (Requires Opt059, 061)
TETRA Radios	
85543	390XOPT115 Auto-Test II Environment for TETRA Radio Systems
90676	390XOPT611 Motorola TETRA MS Auto-Test Software - Includes Opt054 as standard (Requires Opt110, 115)
90943	390XOPT621 Motorola TETRA MTS (Requires Opt115, 111)
P25 Radios	
83373	390XOPT218 Auto-Test II Environment for P25 Radio Systems (Requires Opt200)
87371	390XOPT607 BK Technologies DPHX5102X Series Auto-Test and Alignment Software (Requires Opt218, 061)
91956	390XOPT627 BK Technologies KNG Command Series Auto-Test and Alignment Software; Portables Only (Requires Opt218, 061)
139148	390XOPT636 BK Technologies KNG S-Series (Portables only) Auto-Test and Alignment Software (Requires Opt218, 061)
87372	390XOPT606 EF Johnson ES Series Auto-Test and Alignment Software (Requires Opt218, 061)
112997	390XOPT633 EF Johnson Viking Series Auto-Test and Alignment Software (Requires Opt218, 061)
90966	390XOPT616 L3Harris P25 Series Auto-Test and Alignment Software (Requires Opt218, 061)
91955	390XOPT625 L3Harris P25 ADVANCED Series Auto-Test and Alignment Software (Requires Opt616)
140637	390XOPT637 L3Harris XL Series Auto-Test and Alignment Software (Requires Opt218, 061)
87370	390XOPT605 Icom P25 Auto-Test and Alignment Software (Requires Opt218, 061)
90946	390XOPT608 Kenwood 5x10 Series Auto-Test and Alignment Software (Requires Opt218, 061)
91959	390XOPT630 Kenwood 5x20 Series Auto-Test and Alignment Software (Requires Opt218, 061)
141437	390XOPT641 Kenwood Viking 5/6/7000 Series Auto-Test and Alignment Software (Requires Opt218, 061)
83385	390XOPT600 Motorola ASTRO 25 XTS / XTL Series Auto-Test and Alignment Software (Requires Opt218, 061)
84422	390XOPT602 Motorola ASTRO 25 Series XTL Power Auto-Test and Alignment Software (Requires Opt600 & 112277)

83386	390XOPT601 Motorola ASTRO (XTS-3000) Series Auto-Test and Alignment Software (Requires Opt21, 061)
84421	390XOPT604 Motorola APX Series Auto-Test and Alignment Software (Requires Opt218, 061 & 112277)
140545	390XOPT644 Motorola APX 8000 Series Auto-Test and Alignment Software (Requires Opt604)
140899	390XOPT645 Motorola APX "B" Series Auto-Test and Alignment Software (Requires Opt604)
390XOPT646	390XOPT646 Motorola APX NEXT™ Series Auto-Test and Alignment Software (Requires 604)
91958	390XOPT629 Tait P25 Series Auto-Test ONLY (Requires Opt218, 061)

DMR Radios

83384	390XOPT401 Auto-Test II Environment for DMR Radio Systems (Requires Opt400)
91705	390XOPT626 DMR Repeater Auto-Test Software (Requires Opt401, 061)
91957	390XOPT628 Hytera DMR Series Auto-Test and Alignment Software (Requires Opt401, 061)
141994	390XOPT642 Hytera DMR Repeater Auto-Test (Requires Opt628)
89818	390XOPT610 Motorola MOTOTRBO Radio Series Auto-Test and Alignment Software (Requires Opt401, 061 & 112277)
141377	390XOPT639 Tait DMR Series Auto-Test ONLY (Requires Opt400, 401, 061)

dPMR Radios

84415	390XOPT421 Auto-Test II Environment for dPMR Radio Systems (Requires Opt420)
-------	--

NXDN Radios

84417	390XOPT441 Auto-Test for NXDN Radio Systems (Requires Opt440)
112987	390XOPT632 Icom NXDN Series Auto-Test (Requires Opt441, 061)
91960	390XOPT631 Kenwood NEXEDGE Series Auto-Test and Alignment Software (Requires Opt441, 061)

ARIB T98 Radios

84419	390XOPT461 Auto-Test II Environment for ARIB T98 Radio Systems (Requires Opt460)
-------	--

Multi-Protocol Radios

141378	390XOPT640 Kenwood NX-3000 / 5000 Series Auto-Test and Alignment Software (Requires Opt200 / 218, Opt400 / 401 and / or Opt440 / 441 depending on radio digital technology selected)
--------	--

Languages

84410	390XOPT090 3920 Chinese GUI
-------	-----------------------------

Optional Accessories

89243	Case, Hard Transit with Wheels (Pelican)
10225	Case, Soft Padded Carrying
10228	3920 Accessory Pouch
63936	DMM Test Leads (Category 3 Rated)
112277	10 Amp Current Shunt (0.01 Ohm)
90323	3920 5U Rack Mount Kit
90322	3920 6U Rack Mount Kit
67442	Kit, 10 / 20 dB Pads, TNC
67411	Scope Probe Kit
10456	3920 Front / Rear Cover
63928	DC to AC Converter, 12 VDC to 110-120 VAC
9149	Antenna (BNC) (50 MHz)
82556	Attenuator (6 dB / 150 Watts), 1.5 GHz
82557	Attenuator (10 dB / 150 Watts), 1.5 GHz
58520	50 Ohm 250 Watts 5 GHz Termination
140309	3920 Return Loss Bridge Kit
64009	3920 Microphone
63351	RF Cable for AutoAlignment (COAX ASSY, RG223, 36.0, BNC, M, ST / BNC, M, ST)
63927	Survey Technologies Inc (STI) Site Survey Package (Software & GPS Antenna)

Extended Warranties

84349	3920 1 Year Extended Hardware Warranty + ANSI No-Cert Calibrations
84350	3920 1 Year Extended Hardware Warranty + Certified Calibrations
89738	3920 2 Year Extended Hardware Warranty + ANSI No-Cert Calibrations
89741	3920 2 Year Extended Hardware Warranty + Certified Calibrations
84351	3920 3 Year Extended Hardware Warranty + ANSI No-Cert Calibrations
84352	3920 3 Year Extended Hardware Warranty + Certified Calibrations

Calibration Certificates

83482	CALFB392X 3920 Calibration Certificate (ISO 9001)
-------	---