Data Sheet

# VIAVI AVX-10K

#### Flight Line Test Set

This document defines the performance specifications for the AVX-10K Flight Line Test Set. A 5 minute warm-up period is required for full compliance to all specifications.

#### **DME Mode Specifications**

Signal Generator	
A 5-minute warm-up per	iod is required for all specifications.
Output Frequency	
Reply Frequency	
Range	962 to 1213 MHz
Accuracy	±10 kHz
Output Level	
Antenna Port	
Range	-67 to -2 dBm at Antenna port
Resolution	1 dB
Accuracy	±2 dB
Distance to UUT antenna (ref only)	6 to 300 ft with supplied antenna
RF I/O Port	
Range	-115 to -47 dBm
Resolution	1 dB
Accuracy, -95 dBm to –47 dBm	±1 dB
Accuracy, -115 dBm to <-95 dBm	±2 dB
Reply Pulse Spacing	
P1 to P2	12 µs ±100 ns (X Channel) @ 50% peak
P1 to P2	30 µs ±100 ns (Y Channel) @ 50% peak
Reply Pulse Width	
P1/P2	3.5 μs ±0.5 μs
Echo Reply	
Control	On/Off
Position	30 nmi ±1 nmi
Amplitude	±11 dB ±1 dB relative to reply level



Reply Pulse Rise and Fall Times		
All Pulses		
Rise Time	2.5 µs ±0.25 µs (10% to 90%)	
Fall Time	2.5 µs ±0.25 µs (90% to 10%)	
Reply Delay		
X Channel		
Fixed Reply Delay	50 μs ±100 ns	
Y Channel		
Fixed Reply Delay	56 μs ±100 ns	
Range Delay		
X and Y Channel		
Range	0 to 450.00 nmi	
Resolution	0.01 nmi	
Accuracy	±0.01 nmi	
Range Rate		
X and Y Channel		
Range	10 to 6500 kts	
Resolution	1 kts	
Accuracy	±0.01 % typical, tested to ±0.5%	
Squitter		
PRF	2700 Hz	
Accuracy	±2%	
Distribution	Per ARINC 568	
Reply Efficiency		
Range	0 to 100%	
Resolution	1% increments	
Accuracy	±0.5%	
Ident Tone	1	
Selection	Selectable three letter code	
Frequency	1350 Hz	
Accuracy	±2 Hz	
UUT Measurements		
ERP		
Range	+47 to +64 dBm	
Resolution	0.1 dB	
Accuracy	±2 dB	



### DME Mode Specifications continued

Direct Connection Peak	Pulse Power
Range	+47 to +64 dBm
Resolution	0.1 dB
Accuracy	±1 dB
Frequency	
Range	1025.00 to 1150.00 MHz
Resolution	10 kHz
Accuracy	±20 kHz
Interrogation Pulse Wid	lth
P1 and P2 Pulse Widths	
Range	2.00 to 5.00 µs
Resolution	1 ns
Accuracy	±50 ns
Interrogation Pulse Spa	cing
P1 to P2 Spacing	10 to 14 µs (X Channel)
P1 to P2 Spacing	34 to 38 µs (Y Channel)
Resolution	10 ns
Accuracy	±20 ns
Interrogation PRF	
Range	1 to 300 Hz
Resolution	1 Hz
Accuracy	±2 Hz
	· ·

### **Transponder Mode**

#### Signal Generator

A 5-minute warm-up period is required for all specifications.

		_
RF	Output	Frequency

in output nequency	
Interrogation Frequency	1030 MHz
Accuracy	±10 kHz
RF Output Level	
Antenna Port	MTL + 6 dB typical, automatically controlled for a MTL range of -83 to -68 dBm
Range	-67 to -2 dBm at antenna port
Resolution	0.5 dB
Accuracy	±2 dB
Distance to UUT Antenna	6 to 200 ft with supplied antenna
RF I/O Connector	MTL + 6 dB typical, automatically controlled
Range	-115 to -47 dBm
Resolution	0.5 dB
Accuracy	-95 to -47 dBm (±1 dB)
Accuracy	-115 to <-95 dBm (±2 dB)

ATCRBS/MODE S Inte	rrogation Pulse Spacing
Mode A	
P1 to P2	2.00 μs (±25 ns)
P1 to P3	8.00 μs (±25 ns)
Mode C	
P1 to P2	2.00 μs (±25 ns)
P1 to P3	21.00 µs (±25 ns)
Mode S	
P1 to P2	2.00 μs (±25 ns)
P1 to P6	3.50 µs (±25 ns)
P1 to SPR	4.75 µs (±25 ns)
P5 to SPR	0.40 µs (±50 ns)
Intermode Interrogat	ion Pulse Spacing
Mode A	
P1 to P3	8.00 μs (±25 ns)
P1 to P4	10.00 µs (±25 ns)
Mode C	
P1 to P3	21.00 μs (±25 ns)
P1 to P4	23.00 µs (±25 ns)
Interrogation Pulse W	lidths
Modes A, C, S, Interm	iode
P1, P2, P3	0.80 µs (±50 ns)
Mode S	
P6 (Short DPSK Block)	16.25 μs (±50 ns)
P6 (Long DPSK Block)	30.25 μs (±50 ns)
P5	0.80 µs (±50 ns)
Intermode	
P4 (Short)	0.80 µs (±50 ns)
P4 (Long)	1.60 µs (±50 ns)
Interrogation Pulse R	ise and Fall Times (All Modes)
Rise Time	50 to 100 ns
Fall Time	50 to 200 ns
Phase Modulation (Al	l Modes)
Transition Time	<80 ns
Phase Shift	180° ±10°
SLS Levels (Automation	cally controlled in the SLS LEVEL test)
ATCRBS	
SLS Level (P2)	-9 dB, -1 to +0 dB relative to P1 level
	0 dB, -0 to +1 dB relative to P1 level
	OFF
Mode S	
SLS Level (P5)	-12 dB, -1 to +0 dB relative to P6 level
	+3 dB, -0 to +1 dB relative to P6 level
	OFF
Interrogation Test Sig	inals
Mode S	PRF: 50 Hz (±5 Hz)
ATCRBS	PRF: 235 Hz (±5 Hz)
	<u> </u>

# Transponder Mode continued

UUT Measurements		
ERP (@ 1090 MHz)		
Range	+45.5 to +59 dBm (35.5 to 800 watts)	
Resolution	0.1 dB	
Accuracy	±2 dB	
Direct Connection Peal	v Pulse Power (@ 1090 MHz)	
Range	+46.5 to +59 dBm (45 to 800 Watts)	
Resolution	0.1 dB	
Accuracy	±1 dB	
Transmitter Frequency		
Range	1087.000 to 1093.000 MHz	
Resolution	10 kHz	
Accuracy	±50 kHz	
Receiver Sensitivity, Ra	diated MTL	
Range	-79 to -67 dBm into 0 dBi antenna	
Resolution	0.1 dB	
Accuracy	±2 dB, typical	
Receiver Sensitivity, D	irect Connection MTL	
Range	-79 to -67 dBm	
Resolution	0.1 dB	
Accuracy	±2 dB	
Reply Delay		
ATCRBS		
Range	1.80 to 7.00 µs	
Resolution	10 ns	
Accuracy	±50 ns	
Reply Delay, Mode S a	nd ATCRBS Mode S ALL-CALL	
Range	125.00 to 131.00 µs	
Resolution	10 ns	
Accuracy	±50 ns	
Reply Delay Jitter		
ATCRBS		
Range	0.00 to 2.30 µs	
Resolution	1 ns	
Accuracy	±20 ns	
Mode S and ATCRBS N	10de S ALL-CALL	
Range	0.00 to 6.00 µs	
Resolution	1 ns	
Accuracy	±20 ns	
Pulse Spacing		
F1 to F2		
Range	19.70 to 21.60 µs	
Resolution	1 ns	
Accuracy	±20 ns	
Mode S Preamble		
Range, P1 to P2	0.8 to 1.2 µs	
Range, P1 to P3	3.3 to 3.7 µs	
Range, P1 to P4	4.3 to 4.7 μs	

Resolution	1 ns
Accuracy	±20 ns
Pulse Widths	
F1 to F2	
Range	0.25 to 0.75 µs
Resolution	1 ns
Accuracy	±20 ns
Mode S Preamble	
Range	0.25 to 0.75 µs
Resolution	1 ns
Accuracy	±20 ns
PULSE Amplitude Vari	ation
Range	
Mode S (Relative to P1)	-3 to +3 dB
ATCRBS (Relative to F1)	-3 to +3 dB
Resolution	0.1 dB (0.01 dB via RCI)
Accuracy	±0.5 dB
DF 11 Squitter Period	
Range	0.10 to 4.88 sec
Resolution	10 ms
Accuracy	±10 ms
Diversity Isolation	
Range	0 to >20 dB (depending on test distance)
Test Distance	1.83 m (6ft) to 28.96 m (95 ft)
Resolution	0.1 dB
Accuracy	±3 dB

## TCAS Mode

Signal Generator		
Output Frequency		
Reply Frequency	1090 MHz	
Accuracy	±10 kHz	
Output Level (simulated E	RP)	
Antenna Port <sup>1,2</sup>		
Radiated power at 0 dBi UUT antenna	-68 dBm typical @ 10 nmi (range, automatically controlled)	
Range	-67 to -2 dBm at antenna connector	
Resolution	0.5 dB	
Accuracy	±2 dB	
Distance to UUT antenna	6 to 300 ft. with supplied antenna	
RF I/O Connector		
Automatic Mode	-68 dBm @ 10 nmi (range automatically controlled)	
Manual Mode Range	-115 to -47 dBm	
Resolution	0.5 dB	
Accuracy	-95 to -47 dBm (±1 dB)	
Accuracy	-115 to <-95 dBm (±2 dB)	

### **TCAS Mode continued**

Reply Pulse Spacing	
Mode C	
F1 to F2	20.30 µs ±25 ns
F1 to C1	1.45 µs ±25 ns
F1 to A1	2.90 μs ±25 ns
F1 to C2	4.35 μs ±25 ns
F1 to A2	5.80 μs ±25 ns
F1 to C4	7.25 μs ±25 ns
F1 to A4	8.70 μs ±25 ns
F1 to B1	11.60 µs ±25 ns
F1 to D1	13.05 µs ±25 ns
F1 to B2	14.50 μs ±25 ns
F1 to D2	15.95 μs ±25 ns
F1 to B4	17.40 µs ±25 ns
F1 to D4	18.85 μs ±25 ns
Mode S	·
P1 to P2	1.00 μs ±25 ns
P1 to P3	3.50 μs ±25 ns
P1 to P4	4.50 μs ±25 ns
P1 to D1	8.00 µs ±25 ns
D1 to Dn (n=2 to 112)	1.00 μs times (n-1) ±25 ns
Reply Pulse Widths	·
Mode C	
All pulses	0.45 μs ±50 ns
Mode S	
P1 through P4	0.50 μs ±50 ns
D1 through D112	0.50 μs (±50 ns), 1 μs chip width
Reply Modes	TCAS I / II Mode C (with altitude reporting)
	TCAS II Mode S formats 0, 11, 16
Reply Pulse Amplitudes	·
ATCRBS	±1 dB relative to F1
Mode S	±1 dB relative to P1
Reply Pulse Rise and Fall	Times (All Modes)
Rise Time	30 to 100 ns
Fall Time	30 to 200 ns
Percent Reply	
Range	0 to 100%
Resolution	1%
Accuracy	±1%
Reply Delay	
ATCRBS	3.0 μs ±50 ns
Mode S	128 µs ±50 ns
Range Delay	
Range	0 to 260 nmi
Resolution	0.1 nmi
Accuracy	±0.02 nmi

Range Rate	
Range	-1200 to +1200 kts
Resolution	10 kts
Accuracy	10%
Altitude Range	
Range	-1000 to 126,000 ft.
Resolution, Mode C	100 ft.
Resolution, Mode S	25 ft.
Altitude Rate	
Range	-10,000 to +10,000 fpm
Resolution	100 fpm
Accuracy	10%
Squitter	1
Control	On/Off
Rate	0.8 to 1.2 seconds, randomly distributed
Receiver	
Pulse Spacing (ATCRBS, N	Node C ALL CALL)
S1 to P1	2.0 µs
Accepts	< ±200 ns
Rejects	> ±1.0 µs
P1 to P3	21.0 µs
Accepts	< ±200 ns
Rejects	(<10% Replies) >±1.0 μs
P1 to P4	23.0 µs
Accepts	< ±200 ns
Rejects	(<10% Replies) > ±1.0 µs
Mode S	
P1 to P2	2.0 µs
Accepts	<±200 ns
Rejects	(<10% Replies) >±1.0 μs
P1 to SPR	4.75 µs
Accepts	<±200 ns
Rejects	(<10% Replies) >±1.5 µs
Suppression	
ATCRBS (P2 or S1)	
>0.5 dB above level	<10% Replies
of P1	
UUT Measurements	
ERP (@ 1030 MHz)	
ATCRBS	
Range	+43 to +58 dBm (20 to 631 watts)
Resolution	0.1 dB
Accuracy	±2 dB
Mode S	
Range	+43 to +58 dBm (20 to 631 watts)
Resolution	0.1 dB
Accuracy	±2 dB
Direct Connection Peak P	ulse Power (@ 1030 MHz)
ATCRBS	
Range	+43 to +58 dBm (20 to 631 watts)

### **TCAS Mode continued**

Resolution	0.1 dB
Accuracy	±1 dB
Mode S	
Range	+43 to +58 dBm (20 to 631 watts)
Resolution	0.1 dB
Accuracy	±1 dB
Frequency	
Range	1029.900 to 1030.100 MHz
Resolution	1 kHz
Accuracy	±10 kHz
TCAS Broadcast Inte	rval
Range	1.0 to 12.0 sec
Resolution	0.1 sec
Accuracy	±0.2 sec

#### **UAT Mode**

Signal Generator	
RF Output Frequency	
Transmit Frequency	978 MHz
Accuracy	±10 kHz
Output Level	
Antenna Port	
Radiated power at 0 dbi UUT antenna	-85 dBm, automatically controlled
Range	-67 to -2 dBm at antenna connector
Resolution	0.5 dB
Accuracy	±2 dB
Distance to UUT antenna	6 to 150 ft. with supplied antenna
RF I/O Port	
Automatic mode	-85 dBm
Accuracy	±1 dB
Modulation	
Туре	BPFSK per RTCA DO-282B
Deviation	±312.5kHz typical
UUT Measurements	
ERP (@ 978 MHz)	
Range	+35 to +57 dBm (3.16 to 500 watts)
Resolution	0.1 dB
Accuracy	±2 dB
Test distance	6 to 150 ft with supplied antenna
Direct Connection Peak F	Pulse Power (@978 MHz)
Range	+35 to +57 dBm (3.16 to 500 watts)
Resolution	0.1 dB
Accuracy	±1 dB
Frequency	
Range	977.96 to 978.04 MHz
Resolution	1 kHz
Accuracy	±10 kHz

#### NAV/COMM

Accuracy

±3 dB

RF Output Frequency		
Mode: Single	10.0 MHz to 400.0 MHz in 100 kHz steps	
ILS and VOR Mode		
Marker Beacon Channel	72.0 MHz to 78.0 MHz in 25 kHz steps	
Marker Beacon Preset	74.5 MHz, 75.0 MHz, 75.5 MHz	
Marker Beacon Variable	72.0 MHz to 78.0 MHz in 1 kHz steps	
VOR Channel	108.0 MHz to 117.95 MHz in 50 kHz steps	
VOR Preset	108.0 MHz, 108.05 MHz, 117.95 MHz	
VOR Variable	107.0 MHz to 118.0 MHz in 1 kHz steps	
LOC Channel	108.1 MHz to 111.95 MHz in 50 kHz steps	
LOC Preset	108.1 MHz, 108.15 MHz, 110.15 MHz	
LOC Variable	107.0 MHz to 113.0 MHz in 1 kHz steps	
G/S Channel	329.15 MHz to 335.0 MHz in 50 kHz steps	
G/S Preset	334.25 MHz, 334.55 MHz, 334.70 MHz	
G/S Variable	327.0 MHz to 337.0 MHz in 1 kHz steps	
Comm AM Channel	10.0 MHz to 400.0 MHz in 25 kHz steps (8.33 kHz steps available 118.0 to 156.0 MHz)	
Comm AM Preset	118.0 MHz, 137.0 MHz, 156 MHz	
	225.0 MHz. 312.0 MHz, 400 MHz	
Comm AM Variable	10.0 MHz to 400.0 MHz in 1 kHz steps	
Comm FM Channel	136.0 MHz to 400.0 MHz in 12.5 or 25 kHz steps	
Comm FM Preset	156.0 MHz, 165.0 MHz, 174.0 MHz	
Comm FM Variable	136.0 MHz to 400.0 MHz in 1 kHz steps	
Comm SSB Variable	10.0 MHz to 30.0 MHz in 100 Hz steps	
SELCAL Channel	10.0 MHz to 30.0 MHz, 118.0 MHz to 156.0 MHz in 25 kHz steps	
SELCAL Preset	10.045 MHz, 21.0 MHz, 30 MHz, 118.0 MHz, 137.0 MHz, 156 MHz	
SELCAL Variable	10.0 MHz to 30.0 MHz, 118.0 MHz to 157.0 MHz in 1 kHz steps	
Output Level		
Antenna Port (75 MHz to 400 MHz)		
Single Carrier	+13 dBm to –67 dBm in 0.5 dB steps	
Accuracy	±3 dB	
Dual Mode LOC	0 dBm fixed	
Accuracy	±2.5 dB	
Dual Mode G/S	0 dBm to –76 dBm in 0.5 dB steps	
Accuracy	±3 dB (0 to -67 dBm)	
Tri-Mode Marker	+13 dBm fixed	
Accuracy	±2 dB	
Tri-Mode LOC	–9 dBm fixed	
Accuracy	±2 dB	
Tri-Mode G/S	–9 dBm to –83 dBm in 0.5 dB steps	
Accuracy	±3 dB (±9 to -74dBm)	
Antenna Port (10 MHz to 75 MHz)		
Single Carrier	±17 dBm to –67 dBm in 0.5 dB steps	

### NAV/COMM continued

#### RF I/O Port (75 MHz to 400 MHz)

	- ,
Single Carrier	±12 dBm to –130 dBm in 0.5 dB steps
Accuracy	−12 dBm to −39.5 dBm (±2.5 dB)
	−40 dBm to −94.5 dBm (±2.0 dB)
	−95 dBm to −120 dBm (±3 dB)
Dual Mode LOC	–25 dBm fixed
Accuracy	±2 dB
Dual Mode G/S	–22 dBm to –101 dBm in 0.5 dB steps
Accuracy	±2.5 dB
RF I/O Port (10 MHz to 75 MHz)	
Single Carrier	–40 dBm to –130 dBm in 0.5 dB steps
Accuracy	−40 dBm to −94.5 dBm (±2.0 dB)
	–95 dBm to –120 dBm (±3.0 dB)

#### **VOR Mode**

#### **VOR Tone Frequency Accuracy** 30 Hz Reference ±0.02% 30 Hz Variable ±0.02% 1020 Hz ±0.02% 9960 Hz ±0.02% **AM Modulation** CAL 30 and 9960 Hz Tones 30% AM, each tone Accuracy 1% modulation 1020 Hz Tone 30% AM 1020 Hz Morse Code 10% AM Accuracy ±2% modulation 0 to 55% AM Variable Range 30, 9960, and 1020 Hz Tones Distortion <2.0% in CAL position FM Modulation 30 Hz reference at ±480 Hz peak deviation on 9960 Hz sub-carrier Accuracy ±25 Hz peak deviation To – From Selectable Bearing 0°, 30°, 60°, 90°, 120°, 150°, 180°, 210°, 240°, Preset Bearing 270°, 300° and 330° Variable Bearing 3600 digitally derived courses in 0.1° increments. Accuracy ±0.1°

#### LOC Mode

LOC Tone Frequency Accuracy		
90 Hz	±0.02%	
150 Hz	±0.02%	
1020 Hz	±0.02%	
Modulation		
CAL		
90 and 150 Hz tones	20% AM, each tone	
1020 Hz Audio tone	30% AM	
1020 Hz Morse code	10% AM	
Accuracy	±2% modulation	
Variable Range	0 to 28% AM, 90 and 150 Hz tones	
	0 to 42% AM, 1020 Hz tone	
Distortion	<2.5% in CAL position	
LOC DDM		
Fixed Range	±0, 0.093, 0.155, 0.200 DDM and Tone Delete	
Accuracy	±0.0015 DDM (±1.5 µA) ±3% of setting	
	(≤+10 dBm Output Level)	
Variable Range	±0.4 in 0.001 DDM steps	
Accuracy	±0.0025 DDM (±2.5 µA) ±3% of setting	
	(≤+10 dBm Output Level)	
Variable Sweep (Available only in dual and tri-modes)		
Range	0 to ±30 µA	
Sweep Rates	5 to 40 sec.	
Step Size	5 sec.	
Accuracy	±0.5 sec./sweep	
Phase Shift		
Range	0 to 120 degrees in 5 degree increments (150 Hz phase relative to 90 Hz)	
Accuracy	±0.5°	

#### G/S Mode

G/S Tone Frequency Accuracy		
90 Hz	±0.02%	
150 Hz	±0.02%	
Modulation		
CAL		
90 and 150 Hz tones	40% AM, each tone	
Accuracy	±2% modulation	
Variable Range	0 to 50% AM	
	90 and 150 Hz tones	
Distortion	<2.5% in CAL position	
G/S DDM		
Fixed Range	±0, 0.091, 0.175, 0.400 DDM and Tone Delete	

# G/S Mode continued

Accuracy	±0.003 DDM (±2.5 µA) ±3% of setting (≤+10 dBm Output Level)
Variable Range	±0.8 DDM in 0.001 DDM steps
Accuracy	±0.0048 DDM (±4.0 µA) ±3% of setting (≤+10 dBm Output Level)
Phase Shift	
Range	0 to 120 degrees in 5 degree increments (150 Hz phase relative to 90 Hz)
Accuracy	±0.5°

### Marker Mode

Marker Tone Frequency Accuracy		
400 Hz	±0.02%	
1300 Hz	±0.02%	
3000 Hz	±0.02%	
Modulation		
CAL		
Setting	95% AM	
Accuracy	±5% modulation	
Variable (Single Carrier Only)		
Range	0 to 95% AM	
Distortion		
Single Carrier	0 to 95% AM	
Tri-Mode	<2.5% in CAL position, -67 to +10dBm	
	<5% in CAL position	

#### COMM Mode (AM)

COMM Tone Frequency Accuracy		
1020 Hz	±0.02%	
Modulation		
CAL		
1020 Hz Tone	30% AM	
Accuracy	±2% modulation	
Variable		
Range	0 to 95% AM	
Distortion	< 2.5% in CAL position	

#### COMM Mode (FM)

COMM Tone Frequency Accuracy		
1000 Hz	±0.02%	
Modulation		
CAL		
1000 Hz Tone	5 kHz deviation	
Accuracy	±5%	
Variable		
Deviation Range	1 kHz to 80 kHz	
Distortion	< 5% in CAL position	

## COMM Mode (SSB)

COMM Tone Frequency Accuracy	
1000 Hz	±6.25Hz referenced to carrier
Modulation	
Variable	
Range Upper or Lower SB	25 Hz to 3000 Hz in 25 Hz steps

### COMM Mode (SELCAL)

Provides amplitude modu tones per DO-093A stand	lation with SELCAL (SELective CALling) ard.
SELCAL Tone Frequency Accuracy	±0.02%
Transmit Modes	-
Single	Single transmission
Continuous	7.5 sec. interval (typical)
Modulation	
CAL	
Per SELCAL tone	40% AM
Accuracy	±2% modulation
Variable	
Range	0 to 55% AM
Distortion	< 2.5% in CAL position
SELCAL Tone Frequencie	25
Designator	Audio Frequency (Hz)
A	312.6
В	346.7
С	384.6
D	426.6
E	473.2
F	524.8
G	582.1
Н	645.7
J	716.1
К	794.3
L	881.0
М	977.2
Р	1083.9
Q	1202.3
R	1335.5
S	1479.1
Т	329.2
U	365.2
V	405.0
W	449.3
X	498.3
Y	552.7
Z	613.1
1	680.0
2	754.2

#### **SELCAL Tone Frequencies continued**

3	836.6
4	927.9
5	1029.2
6	1141.6
7	1266.2
8	1404.4
9	1557.8

#### **Meter Functions**

#### Power Meter (RF I/O Port)

Frequency Range	10.0 MHz to 400 MHz
Power Range	0.1 to <1 W Resolution: 0.01W
	1 to <100 W Resolution: 0.1W <sup>3</sup>
	100 to 1999 W Resolution: 1W <sup>3</sup>
Accuracy	±8% of reading ±1 count (100 to 400 MHz) <sup>4</sup>
	±12% of reading ±1 count (<100 MHz) CW only <sup>4</sup>
Duty Cycle	
≤10 W	Continuous
>10 W to ≤20 W	3 minutes on, 2 minutes off
>20 W to ≤30 W	1 minute on, 2 minutes off
Frequency Measurement	(COMM mode)
Antenna and RF I/O Port	
Range	10 MHz to 400 MHz (depending on Mode)
Resolution	100 Hz
Accuracy	Same as time base ±1 count
Sensitivity	
Antenna Port	≥-35 dBm
RF I/O Port	≥ 0 dBm
AM Meter	
Audio Range	50 Hz to 3000 Hz
Percent Modulation Range	10 to 99%
Accuracy	±10% of reading
Sensitivity	
Antenna Port	≥ -20 dBm
RF I/O Port	≥+15 dBm
FM Meter	
RF Frequency Range	136 to 512 MHz
Audio Range	50 Hz to 3000 Hz
Deviation Range	1 to 15 kHz
Accuracy	±(0. 4 kHz + 8% of reading)
Sensitivity	·
Antenna Port	≥-35 dBm
RF I/O Port	≥ 0 dBm

#### ELT

#### 

#### 406 MHz Beacon Monitor

Sensitivity	
Antenna Port	≥-35 dBm
RF I/O Port	≥ 0 dBm

### SWR/DTF (SWR Port)

SWR Meter		
Frequency Range	10.0 MHz to 1250.0 MHz	
Measurement Range	1 to 7 for SWR	
Accuracy		
SWR < 3:1	±0.2 ±20% of reading	
SWR ≥ 3:1	±0.3 ±20% of reading	
Distance to Fault (DTF)		
Measurement Range	3 to 300 ft, 1 to 100 M	
Accuracy	±1.5 ft + 1% of distance	

### **Misc. Inputs/Outputs**

RF I/O	
Туре	Input/Output
Impedance	50 $\Omega$ typical
Maximum Input Level	4 kW peak, 10 W average
VSWR	<1.3:1
Antenna	
Туре	TNC, Input/Output
Impedance	50 $\Omega$ typical
Maximum Input Level	10 W peak, 0.5 W average
VSWR (30 to 1213MHz)	<1.7:1
SWR	
Туре	TNC, Input/Output
Impedance	50 W typical
Maximum Input Level	20 mW max, 0V DC
VSWR	<1.5:1
Test Antenna	
VSWR	<1.5:1
Gain	8 dB, Typical
Time Base (TCXO)	
Temperature Stability	±1 ppm
Aging	±1 ppm per year
Accuracy	±1 ppm
Battery	
Туре	Li lon
Duration	>4 hrs continuous operation
	>8 hrs, Typical
Input Power (Test Set)	1
Input Range	11VDC-16VDC
Power Consumption	<60W Max
Input Power (Supplied E	xternal AC to DC Converter)
Input Range	100 to 250 V AC, 1.5 A Max, 47 to 63 Hz
Mains Supply Voltage Fluctuations	<10% of the nominal voltage
Transient Over-voltages	According to Installation, Category II

### **Environmental**

Test Set		
Use	Pollution Degree 2	
Altitude	≤4800 meters	
Operating Temp.	-20°C to 45°C (-4° to 113°F) Continuous Use ≥45°C to 55°C (113° to 131°F) Intermittent Use (protected by automatic shutdown)	
Battery Charging Temp. Range	5°C to 40°C (controlled by internal charger)	
Storage Temp.	-30°C to 71°C (-22° to 159.8°F)	
Relative Humidity	95% (±5%) from 5° to 30°C (41° to 86°F) 75% (±5%) from 30° to 40°C (86° to 104°F) 45% (±5%) from 40° to 55°C (104° to 131°F)	
Supplied External AC to DC Converter		

••	
Use	Indoors

## **Physical Characteristics**

Dimensions	
Height	12 in. (30.48 cm)
Width	5.3 in. (13.5 cm)
Depth	4 inches (10.2 cm)
Weight (Test set only)	6.5 lb (2.94 kg)

## Certifications

Test Set		
Altitude, operating	MIL-PRF-28800F, Class 2	
Altitude, not operating	MIL-PRF-28800F, Class 2	
Bench Handling	MIL-PRF-28800F, Class 2	
Blowing Dust	MIL-STD-810F, Method 510.4, Procedure 1	
Drip-proof	MIL-PRF-28800F, Class 2	
Explosive Atmosphere	MIL-STD-810F Method 511.4, Procedure 1	
Safety Compliance	UL-61010B-1, EN 61010-1, CSA 22.2 No 61010-1	
EMC	EN 61326	
Relative Humidity	MIL-PRF-28800F, Class 2	
Shock, Functional	MIL-PRF-28800F, Class 2	
Vibration Limits	MIL-PRF-28800F, Class 2	
Temp, operating	MIL-PRF-28800F, Class 2⁵	
Temp, not operating	MIL-PRF-28800F, Class 2 (with battery removed) <sup>67</sup>	
Transit Drop	MIL-PRF-28800F, Class 2	
External AC-DC Converter		
Safety Compliance	IEC 60950-1:2006 UL/EN 62368-1:2014	
EMI/RFI Compliance	FCC PART 15 CLASS B ISED ICES-003 Issue 6 CISPR32: 2012 EN55032: 2012 VCCI LEVEL II	
RoHS Compliance	2011/65/EU	

<sup>1</sup>Simulates a 50.5dBm XPDR ERP at 10nMi range.

- <sup>2</sup>Level automatically controlled based on actual distance to UUT antenna.
- <sup>3</sup>External attenuator required for input power greater than 30W.

<sup>4</sup>Accuracy specification excluding external attenuator

<sup>5</sup> Temperature range extended to -20°C to 55°C.  $^{\rm 6}$  Temperature range reduced to -30°C to 71°C.

<sup>7</sup>Li Ion Battery must be removed below -20°C and above 60°C.