

MICRO-OHMMETERS

10A

AvionTEq
www.avionteq.com

MODEL 6255

Accurate results within 0.05%. Provides extended test time at 10 Amps without overheating

SPECIFICATIONS

| MODEL | 6255 | | | | | | |
|------------------|--|-------------------------|--------------------------|---------------------------|-------------------------|--------------------------|---------------------------|
| Range | 5.0000 mΩ | 25.000 mΩ | 250.00 mΩ | 2500.0 mΩ | 25.000 Ω | 250.00 Ω | 2500.0 Ω |
| Accuracy | ±0.15% of Reading + 1.0μΩ | ±0.05% of Reading + 3μΩ | ±0.05% of Reading + 30μΩ | ±0.05% of Reading + 0.3mΩ | ±0.05% of Reading + 3mΩ | ±0.05% of Reading + 30mΩ | ±0.05% of Reading + 300mΩ |
| Resolution | 0.1μΩ | 1μΩ | 10μΩ | 0.1mΩ | 1mΩ | 10mΩ | 100mΩ |
| Test Current | 10A | | | 1A | 100mA | 10mA | 1mA |
| Measurement Mode | Selectable: Inductive (continuous test), Resistive (instantaneous test) or Auto (multiple tests) | | | | | | |
| Metal Type Alpha | Selectable: copper, aluminum or other metal Programmable from 000.00 to 99.99 | | | | | | |
| Alarms | Two – programmable set points from 0.0 to 2500.0Ω | | | | | | |
| Memory | Stores up to 1500 test results; data in memory can be reviewed on the instrument display, on a PC or via direct printout | | | | | | |
| Power Source | Rechargeable 6V, 8.5Ah NiMH battery pack (included) | | | | | | |
| Battery Life | Approximately 5000 10A tests | | | | | | |



cover closed



cover open



DataView®

FEATURES

- Measure from 1μΩ (0.1μΩ resolution) to 2500.0Ω
- Test current selection of 1mA, 10mA, 100mA, 1A and 10A
- RTD temperature probe to check tested sample (optional)
- Selectable metal types
- Automatic and manual temperature correction
- Two programmable alarm set points

ACCESSORIES/REPLACEMENTS

CATALOG #1017.84 Kelvin Clips 10 ft (10A - Hippo)

CATALOG #2118.70 Kelvin Clips 20 ft (10A - Hippo)

CATALOG #2118.73

Kelvin Probes 10 ft (1A, Spring Loaded)

CATALOG #2118.74

Kelvin Probes 20 ft (1A, Spring Loaded)

CATALOG #2118.75

Kelvin Probes Pistol Grip 10 ft (10A, Spring Loaded)

CATALOG #2118.76

Kelvin Probes Pistol Grip 20 ft (10A, Spring Loaded)

CATALOG #2118.77

Kelvin Probes 10 ft (10A, Spring Loaded)

CATALOG #2118.78

Kelvin Probes 20 ft (10A, Spring Loaded)

CATALOG #2118.79

Kelvin Clips 10 ft (1-10A) / Replacement for Cat. #2118.71

CATALOG #2118.80

Kelvin Clips 20 ft (1-10A) / Replacement for Cat. #2118.72

CATALOG #2118.82

Kelvin Clips 10 ft (1-10A)

CATALOG #2119.45

Cable, PC RS-232, DB9 F/F 6 ft Null Modem Cable

CATALOG #2129.95

RTD Temperature Probe (plug into faceplate for ambient temperature)

CATALOG #2129.96

RTD Temperature Probe with 7 ft extension cable



- Stores up to 1500 test results
- Selectable inductive or resistive test modes
- Automatic multiple test mode (multiple tests without pressing the test button)
- Large multi-line electroluminescent display
- Local or remote test setup and control
- Internal rechargeable batteries conduct up to 5000 – 10A tests
- Rugged, double insulated watertight case
- Includes FREE DataView® software for data retrieval, real-time display, analysis and report generation

PRODUCT INCLUDES

Extra large tool bag, RS-232 DB9 F/F 6ft null modem cable, RS-232 to USB adapter, US 115V power cord, NiMH rechargeable battery pack, Quick Start Guide, and a USB thumb drive supplied with a user manual and DataView® software.



CATALOG NO. DESCRIPTION

| | |
|---------|---|
| 2129.84 | Micro-Ohmmeter Model 6255 (10A, Instantaneous, Continuous, Multiple Test, Manual/Auto Temperature Compensation; includes 10 ft Kelvin Clips (10A-Hippo, Cat #1017.84), 10 ft Kelvin Probes (1A Spring Loaded, Cat #2118.73) and DataView® Software) |
| 2131.03 | Micro-Ohmmeter Model 6255 (10A, Instantaneous, Continuous, Multiple Test, Manual/Auto Temperature Compensation, and DataView® Software) |



Technical Assistance (800) 343-1391

www.aemc.com