

# Avionics

## DT350H HONEYWELL ASCB ANALYZER



### Supports all versions of Honeywell/GAMA Avionics Standard Communications Bus

The DATATRAC 350H is a portable, battery operated, handheld bus analyzer supporting all versions of the Honeywell/GAMA ASCB Bus.

The DT350H is programmed with the data defined in the ASCB-A, B and C applications specifications, allowing the unit to display receive and transmit data in their scaled units. The scaling database can be reprogrammed with modified or custom data by the user via an RS-232 port and PCMGR-300. This is an optional PC-based program that allows up to 128 setups to be stored in the DT350H's FLASH ROM. In addition, the user may program up to 5 setups into RAM through the front panel keypad. Both types of setup tables support all features of the DT350H (receive, record, break and transmit).

The DT350H has two receive modes, SELECT and ALL. SELECT Mode allows the user to define up to 32 unique words to be captured for each channel. The data can be output to the screen, the RS-232 port, or the built-in 12 bit DAC port. ALL MODE displays all bus address activity on the screen. Two independent receive ports allow connection to primary and/or backup buses to monitor activity simultaneously.

Receive words may be displayed in their predefined scale format from the database or in HEX, Binary, bcd, or a user defined format.

The DT350H has a very powerful breakpoint feature. Receive data can be captured based on up to two breakpoint words which can be programmed to occur independently or in a specific sequence.

The break conditions (=,! =,OR, >, <) can be split between one or both channels with an event count qualifier of up to 99 occurrences before break.

#### FEATURES

- ASCB-A, B, and C in one unit
- Two receive and one transmit port
- Easy menu-driven setup allows intuitive control of unit
- Reprogrammable scaling database
- Powerful RECORD and BREAKPOINT modes
- Four hours of operation from internal battery or operation from 110-220 VAC
- RS-232C and DAC interfaces

## GENERAL SPECIFICATIONS

---

### RECEIVER OPERATION

---

#### Ports

2 Independent

#### Modes

SELECT, ALL

#### Time Stamp

1 ms resolution

#### Word Display Format

Binary, HEX, Eng. Units, BCD, User, Graph

#### Select Word Positions

32

#### Bus Activity Monitor

Monitors loss of address/word

#### Real-time Download

RS-232C or 12-bit D/A

### TRANSMITTER OPERATION

---

#### Ports

1 configurable: version A transmits data and clock on 1 bus only;

Version B transmit data on 1 bus only; Version C transmit data on 1 primary and 1 backup bus

#### Modes

USER, CONTROLLER compatible transmit mode

#### Unique Addresses

16

#### Dynamic Data

10 Words, programmable rise, fall and hold times

#### Fresh Counter

3 or 4 bit

#### Software Checksum/CRC

Calculated dynamically

### BREAKPOINT OPERATION

---

#### Sequence

2: A, B, A or B; A then B

#### Data Conditions

EQ, NEQ, OR, GT, LT

#### Trigger Output

5 V, 20  $\mu$ S via D/A

#### Time Stamp

10 ms resolution

#### Record History

Up to 35,000 programmable about the breakpoint, Event Count1 to 99 before break

#### Review/Playback

Data display, RS-232, Graph, D/A

### RECORD OPERATION

---

#### Record History

Up to 55,000 data words, Sample Interval 2 ms to 10 sec

Review/Playback Data display, RS-232, Graph, D/A

### GENERAL

---

#### Compatibility

ASCB-A, B, and C USER compatible for receive and transmit, controller compatible transmit mode

#### Database

Preprogrammed ASCB-A, B, and C applications and specifications and custom upload capable via PCMGR-300

#### Setup Storage

5 RAM tables, 128 FLASH ROM tables (FLASH tables require PCMGR-300)

### PHYSICAL CHARACTERISTICS

---

#### Weight

3.8 lbs (1.7 kg)

#### Height

6.5" (16.5 cm)

#### Width

9.75" (24.7 cm)

#### Depth

2.0" (5.0 cm)

#### Display

Super-twist, back-lit LCD; 16-line x 40 characters, 240 x 128 dot graphics

#### Power Requirements

110-220 VAC Adapter, internal

NiCad battery (4 hours)

#### Temperature

0 to -50 degrees C operating;

-10 to 60 degrees C storage

## **ORDERING INFORMATION**

---

DT350H-110 ASCB Databus Analyzer (110V)

DT350H-220 ASCB Databus Analyzer (220V)

### **Standard Accessories**

Battery charger, carrying case, Operations Manual

### **Optional Accessories**

ACPCMGR-300 Software support for the DT350H

### **Extended Warranty**

WDTRC/203C Extended standard warranty 36 months with scheduled calibration

WDTRC/205C Extended standard warranty 60 months with scheduled calibration

**CHINA Beijing**

Tel: [+86] (10) 6467 2761 2716  
Fax: [+86] (10) 6467 2821

**CHINA Shanghai**

Tel: [+86] (21) 6282 8001  
Fax: [+86] (21) 62828 8002

**FINLAND**

Tel: [+358] (9) 2709 5541  
Fax: [+358] (9) 804 2441

**FRANCE**

Tel: [+33] 1 60 79 96 00  
Fax: [+33] 1 60 77 69 22

**GERMANY**

Tel: [+49] 8131 2926-0  
Fax: [+49] 8131 2926-130

**HONG KONG**

Tel: [+852] 2832 7988  
Fax: [+852] 2834 5364

**INDIA**

Tel: [+91] 80 5115 4501  
Fax: [+91] 80 5115 4502

**KOREA**

Tel: [+82] (2) 3424 2719  
Fax: [+82] (2) 3424 8620

**SCANDINAVIA**

Tel: [+45] 9614 0045  
Fax: [+45] 9614 0047

**SPAIN**

Tel: [+34] (91) 640 11 34  
Fax: [+34] (91) 640 06 40

**UK Burnham**

Tel: [+44] (0) 1628 604455  
Fax: [+44] (0) 1628 662017

**UK Stevenage**

Tel: [+44] (0) 1438 742200  
Fax: [+44] (0) 1438 727601  
Freephone: 0800 282388

**USA Wichita**

Tel: [+1] (316) 522 4981  
Fax: [+1] (316) 522 1360  
Toll Free: 800 835 2352

**USA New Century**

Tel: [+1] (913) 764 2452  
Fax: [+1] (913) 782 5104



As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2006.

[www.aeroflex.com](http://www.aeroflex.com)  
[info-test@eroflex.com](mailto:info-test@eroflex.com)



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.