



**Automated Pitot Static Tester, Wifi-enabled: 3-Outputs**

*Specifications on back*

## Model 6600-NG Automated Pitot Static Tester with 3 Outputs (WiFi-enabled)

The 6600-NG Automated Tester is ideal for use on aircraft with "Smart Probes" capable of measuring AOA using Air Data. The tester has one Static output (Ps1), one Pitot output (Pt) and a third output (Ps2) which can be used to simulate either AOA or AOS. Using the small and light-weight Remote unit a user can operate the tester from the cockpit and test the entire pitot and static system of the aircraft. An optional internal battery is available. A wide operating temperature option is also available. The high accuracy of this unit meets all RVSM requirements. Also, it requires no maintenance other than to be calibrated only once a year. The use of "Profiles" makes it possible for the operator to run through a test using only a single key on the Remote unit. The 6600-NG is also WiFi-enabled and can be operated wirelessly using an iPad.

### Specifications

#### Ps1 Output

##### Pressure function

range:	0.1 to 42 inHg
resolution:	0.0001 inHg
accuracy:	0.002 inHg

##### Altitude function

range:	-4000 ft. to 60,000 ft.
resolution:	1 foot
accuracy:	2 ft. @ 0 ft; 6 ft. @ 35,000 ft. 12 ft. @ 50,000 ft.

##### Climb function

range:	0 ft/min to 25,000 ft/min
resolution:	1 ft/min
accuracy:	1% of rate of climb

##### Displayed units:

Feet, meters, inHg, mbar, psi, kpa, mmHg.

#### Ps2 Output

**Pressure function:** Same as for Ps1 Output

**Altitude function:** Same as for Ps1 Output

**Climb function:** Same as for Ps1 Output

##### Airspeed function:

range:	0 to 500 knots
resolution:	0.1 knots
accuracy:	0.3 knots @ 50 knots 0.16 knots @ 100 knots 0.05 knots @ 500 knots
<b>Displayed units:</b>	(Diff. or Abs.) inHg, mbar, psi, Kpa, mmHg. Feet, meters, knots, kmph

#### Pt Output

##### Pressure function

range:	0 to 30 inHg (differential)
resolution:	0.0001 inHg
accuracy:	0.003 inHg

##### Airspeed function

range:	0 to 690 knots
resolution:	0.1 knots
accuracy:	0.3 knots @ 50 knots 0.2 knots @ 100 knots 0.03 knots @ 690 knots

##### Mach function

range:	0.0 to 3.0 Mach
resolution:	0.001 Mach
accuracy:	0.001 above 0.2 Mach

##### Displayed units:

knots, Mach, kmph, mph, EPR,  
(Diff. or Abs.) inHg, mbar, psi, kpa, mmHg

#### "Jog" feature

Allows set-point to be increased or decreased in steps of 1 foot or 1 knot simply by using the arrow keys.

#### "Profiles" feature

A profile of the standard set-points of an altimeter check or airspeed check can be downloaded from a computer. Such a profile allows the user to operate the unit using a single key. Up to 10 such profiles can be stored in the unit. PC-based software is included.

#### Pressure & Vacuum system

The tester includes separate pressure and vacuum diaphragm pumps for higher reliability. The pressure system includes a membrane dryer, and a filter to provide clean dry air for the entire system.

#### Remote unit

The Remote unit is the operator interface for the tester. It is small and light enough to be used in the cockpit. The tester can be turned On and Off from the Remote. All valid parameters, including altitude, climb and airspeed, are clearly displayed simultaneously on a single screen on the Remote. An iPad can also be used as a wireless remote unit.

#### Manual Vent

The tester includes manual metering valves to enable the system (aircraft) to be manually vented in the event of loss of power.

#### Power requirement

90-260 VAC, 47-440 Hz ; 100 W (200W with heaters)  
Optional internal battery: 6-8 hours of operation

#### Interfaces

WiFi, RS232 Standard; Encoder optional

#### Dimensions & weights

Main unit: 22" x 14" x 9" / 38 lbs  
Remote unit: 6" x 6" x 1" / 1.8 lbs.

#### Environmental specs:

Operating temp.	0° to 50°C ; -40° to 50°C (optional)
Storage temp.	-40° to 75°C
Humidity:	5 to 100%

*Specifications subject to change without notice*

