



Test with full trust

[www.avionteq.com](http://www.avionteq.com)

<b>Quick Technical Features Comparison</b>		
	<b>ADSE 743</b>	<b>DPS 450</b>
Altitude Range	-2 300 to 80 000 ft	-2 000 to 55 000 ft
Altitude Rate	Max ±15,000ft/min	Max ±6,000ft/min
Max Speed	10 to 850kts	10 to 650kts
Weight	37.4 lb -17 kg	33 lb -15 kg

	<b>DPS450</b>	<b>ADSE 743</b>
<b>LEAK MEASURE FACILITY</b>	X	X
<b>FULL AUTOMATIC MICROPROCESSOR CONTROL</b>	X	X
<b>KEYBOARD DATA ENTRY</b>	X	FULL TOUCH SCREEN
<b>CONTROLLED CLIMB/DECENT RATE</b>	X	X
<b>AUTOMATIC "GO TO GROUND" FUNCTION</b>	X	X
<b>AUTO INTERVENTION (FOR EXCESSIVE LEAKS)</b>	X	X
<b>REMOTE CONTROL</b>	OPTION	STANDARD
<b>MANUALLY OPERATED LID PS/PT MANIFOL</b>	X	
<b>DATA SAVED</b>	X	USB BACK UP
<b>TEMPERATURE USE</b>	41 to 95 F	14 to 104 F
<b>AUTOMATIC PROGRAMS</b>	X	X
<b>BATTERY (opt.)</b>		X
<b>DIRECT CONNECTION TO PC IF NEEDED</b>		X
<b>AoA TESTING (opt. / ADSE744)</b>		X
<b>MODE-S TESTING (opt.)</b>		X
<b>SENSOR</b>	RVSM	RVSM TAPT Thermoregulated Pressure Sensor
<b>EXTENDED RANGE (1000kts) (opt.)</b>		X
<b>CUSTOM CONNECTORS</b>		X