

Avionics

T1200B ARINC 429 CONTROL DISPLAY UNIT



The one test set that covers the entire spectrum of the avionics industry

- External 12 inch touch-screen display allows main unit to be located away from operation
- PS-2 style mouse may be used with or without touch-screen
- May be ordered with front or rear display connectors
- Easy-to-use menu selection of avionics test formats
- Test formats that follow specific OEM avionics CMM's
- Up to 10 words transmitted on each channel
- Transmission and reception of all ARINC 429 words
- Ability to decode VOR, ILS, ADF, VHF, HF, DME, LRA, and ATC associated words as well as all other BCD and BNR data words into easily recognizable engineering units
- Two low speed and two high speed ARINC 429 transmitter/receiver cards

The venerable T1200, a mainstay in avionics' shops worldwide, has been upgraded to extend its reliability and service life. The display has been replaced by a more reliable, external, touch sensitive color Liquid Crystal Display (LCD). Any system utilizing the ARINC 429 databus can be served with the universal T1200B CDU (Control Display Unit). The result is an unprecedented level of equipment compatibility - from on-board systems all the way through bench testing and sub-component applications.

A touch is all it takes. The "User Configuration" menu permits user selection of data to be transmitted or display of data received.

The T1200B CDU also offers these advantages:

- ARINC 429 Avionics Systems. With appropriate optional interface panels, it is compatible with all major makes of navigation / communication equipment.
- On-board Electrical Systems. This includes control and display functions such as operating or directional lights, electrical switching and cockpit display panels, etc.

GENERAL SPECIFICATIONS

RECEIVER OPERATION

LOW SPEED

Meets or exceeds ARINC 429 specifications

Bit Rate

25 KBPS maximum

Word Rate

0.5 to 400 words per second

HIGH SPEED

Meets or exceeds ARINC 429 specifications

Bit Rate

150 KBPS maximum

Word Rate

0.5 to 400 words per second

TRANSMITTER OPERATION

LOW SPEED

Meets or exceeds ARINC 429 electrical specifications

Bit Rate

8.1 to 20.4 KBPS in 9 steps

Accuracy

$\pm 1 \mu s$

Word Rate

5.0 ms to 32,000 ms in 1.0 ms increments

Accuracy

$\pm 0.5 ms$

Max. Word Rate

300 words per second

HIGH SPEED

Meets or exceeds ARINC 429 specifications

Bit Rate

80/100/125 KBPS

Accuracy

$\pm 1 \mu s$

Word Rate

5.0 ms to 32,000 ms in 1 ms

Accuracy

$\pm 0.5 ms$

Max. Word Rate

1500 words per second

PHYSICAL CHARACTERISTICS

MAIN UNIT

Weight

18.0 lbs. (8.16 kg)

Size

7.0"H x 19.0"W x 16.0"D (rack mount)

(17.8 cm x 48.25 cm x 40.6 cm)

Power Requirements

50-60 Hz, 100-240 VAC

DISPLAY (W/ RESISTIVE TOUCH SCREEN)

Weight

7.5 lbs. (3.4 kg)

Size

12.2"H x 12.3"W x 5.7"D

(31 cm x 31.25 cm x 14.5 cm)

Power Requirements

50-60 Hz, 100-240 VAC

VERSIONS, OPTIONS AND ACCESSORIES

When ordering please quote the full ordering number information.

ORDERING INFORMATION

90670	T1200B ARINC 429 Control Display Unit (110 V)
934	T1200B-RC ARINC 429 Control Display Unit - Rear Display Connectors (110 V)

Units come standard with two low speed and two high speed TX and RX ports

Discrete Function Interface Units (DFIU)

935	T1201 ADF/VOLR/MB/ILS/Thomson MMR DFIU
936	T1202 HF/VHF DFIU
937	T1203 DME/XPDR/LRA DFIU
938	T1204 RDMI/RMI//DDI/RAI DFIU
939	T1205A Control Head DFIU
941	T1207 GPS/MLS DFIU

T1200 DFIU cables and overlays are dependent upon unit under test (UUT). Contact Aeroflex for availability.

Standard Accessories

75610	Manual Operations, T1200B CDU
29972	Power Cord, 3 cord 125u 10a
58283	Cable DFIU T1200

Optional Accessories

89815	AC501200B5 Monitor Support Bracket
-------	------------------------------------

Used to mount display on front of the T1200B for rack mounted systems

30074	Power Cord EUR 10a 230 V
-------	--------------------------

Extended Warranty

87313	WT1200B/203C Extended standard warranty 36 months with scheduled calibration
87314	WT1200B/205C Extended standard warranty 60 months with scheduled calibration

CHINA Beijing

Tel: [+86] (10) 6539 1166
Fax: [+86] (10) 6539 1778

CHINA Shanghai

Tel: [+86] 21 2028 3588
Fax: [+86] 21 2028 3558

CHINA Shenzhen

Tel: [+86] (755) 3301 9358
Fax: [+86] (755) 3301 9356

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 89 99641 0
Fax: [+49] 89 99641 160

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 [4] 115 4501
Fax: [+91] 80 [4] 115 4502

JAPAN

Tel: [+81] (3) 3500 5591
Fax: [+81] (3) 3500 5592

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SINGAPORE

Tel: [+65] 6873 0991
Fax: [+65] 6873 0992

TAIWAN

Tel: [+886] 2 2698 8058
Fax: [+886] 2 2698 8050

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2011.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.