

Avionics

UC-584

Universal Transponder Antenna Coupler



Time-saving transponder antenna coupler, providing repeatable test results on the ramp or in the hangar

- Reliable FAR Part 43 Appendix 'F' ERP and MTL testing in high multi-path environments
- Provides >20 dB of antenna isolation for Mode S transponder altitude and diversity tests
- <1 dB repeatability
- Rugged design for ramp use
- Fits most 'Shark Fin' L-Band antenna's
- Quick action antenna grip/release action

TRANSPONDER ANTENNA COUPLER

The UC-584 Universal Transponder Antenna Coupler is designed to solve the problem of reliable FAR Part 43 Appendix 'F' ERP (Effective Radiated Power) and transponder MTL (Minimum Trigger Level) testing, in the high multi-path ramp and hangar environments. The Antenna Coupler mounts directly over the aircraft transponder antenna and is retained in place with a toggle action grip.

The Antenna Coupler provides 20 dB of transponder antenna isolation, ensuring airborne TCAS systems and SSR ground stations do not see UUT transponder altitude replies under test conditions where the air-data system is pressurized to flight levels. ADS-B transponder antennas exhibit gain in the forward direction, which adds to the complication of where to position test antennas in relation to the aircraft antenna to achieve a repeatable ERP test. The innovative design of the Antenna Coupler includes an integral positioning slot ensuring a high level of measurement repeatability is achieved, saving test time.

The UC-584 can be connected to the Aeroflex IFR 6000/6015 direct connect port. The coupler's 1.5 dB insertion loss may be compensated for by adding this amount to the setup menu cable loss parameter.

SPECIFICATIONS

TRANSPONDER ANTENNA COUPLER

Frequencies

1030 MHz, 1090 MHz

Return Loss

>7.71 dB at both the antenna under test input and coupler input

Insertion Loss

0.6 dB \pm 0.5 dB

Repeatability

<1 dB

Isolation

>20 dB

Connector

TNC Female

PHYSICAL CHARACTERISTICS

DIMENSIONS

Height

5.25 inches (13.3 cm)

Width

5.75 inches (14.6 cm)

Depth

8.25 inches (20.9 cm)

Weight

2 lbs (0.9 kg)

ORDERING INFORMATION

When ordering, please include the Order Number listed below:

Ordering

Numbers	Description
86931	UC-584 Universal Transponder Antenna Coupler

CHINA Beijing

Tel: [+86] (10) 6539 1166
Fax: [+86] (10) 6539 1778

CHINA Shanghai

Tel: [+86] (21) 5109 5128
Fax: [+86] (21) 5150 6112

CHINA Shenzhen

Tel: [+86] (755) 3301 9358
Tel: [+86] (755) 3301 9356

FINLAND

Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE

Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY

Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG

Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA

Tel: [+91] 80 [4] 115 4501
Fax: [+91] 80 [4] 115 4502

KOREA

Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA

Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

UK Stevenage

Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA

Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2010.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.