

To buy, sell, rent or trade-in this product please click on the link below:  
[www.avionteq.com/BriskHeat-ACR-4-DB240KIT-Dual-Zone-Hot-bonder-kit](http://www.avionteq.com/BriskHeat-ACR-4-DB240KIT-Dual-Zone-Hot-bonder-kit)



	<b>ACR-3-D__KIT</b>	<b>ACR-4-DB__KIT</b>
<b>Display Size</b>	8.4 in (213 mm)	10.1 in (256 mm)
<b>Display Content</b>	Displays 1 zone at a time	Displays both zones when both operational
<b>TC Leads</b>	30 gage wire x 6 ft long	24 gage wire x 6 ft long
<b>Thermocouple Boxes</b>	Built into Hot Bonder	Removeable with standard 15 foot CAT 5 Cable stored internally (replaceable)
<b>Thermocouple Function</b>	Control and/or alarm	Control and/or Alarm, or Monitor Only
<b>Program/Recipe Storage</b>	30 programs	Unlimited
<b>Recipe Steps</b>	3 ramp/soak steps, cooldown	Unlimited ramp/soak steps, with cooldown
<b>Heat Source (Blanket Information)</b>	No information recorded	Heating blanket information stored and resistance checks performed; data recorded
<b>Sensor Type</b>	Type-J (30 gage) with Mini Connector - 10 per zone	Type-J (24 gage) with Standard Connector - 10 per zone
<b>Data Storage</b>	Last 12 cures saved	Last 60 cures saved
<b>Data Transfer</b>	USB	USB
<b>Realtime printing</b>	1 per zone with replaceable ribbon	1 for both zones with thermal paper
<b>Ethernet Connection (external)</b>	None	Yes, for future expansion
<b>Display Units of Measure</b>	Degrees (°F, °C); Pressure (inHG, mmHG, mbar)	Degrees (°F, °C); Pressure (inHG, mmHG, kPa, mbar)
<b>Vacuum Pump</b>	(2) 28 inHG	(1) 29 inHG
<b>Venturi Pump</b>	(2) 28 inHG	(2) 28 inHG
<b>Base Dimensions (dual)</b>	22 x 18 x 10 in; 48 lbs (559 x 457 x 254 mm; 22 kg)	23 x 18 x 12 in; 46 lbs (584 x 457 x 305 mm; 21 kg)
<b>Accessory Kit Dimensions (w/heaters)</b>	19 x 15 x 7 in; 45 lbs (483 x 381 x 178 mm; 21 kg)	20 x 16 x 10 in; 48 lbs (508 x 406 x 254 mm; 22 kg)