

To buy, sell, rent or trade-in this product please click on the link below:

<https://www.avionteq.com/Nav-Aids-Ltd-DH8-834M-Air-Data-Accessory-Kit-for-Dash-8-100-200-300-400-Aircraft.aspx>

**AvionTEq**

Trusted Test Equipment Solutions

[www.avionteq.com](http://www.avionteq.com)

**AIR DATA ACCESSORIES KIT  
MODEL No. DH8-834M  
DASH8-100/200/300/400  
AIRCRAFT**



## AIR DATA ACCESSORIES KIT MODEL No. DH8-834M DASH8-100/200/300/400 AIRCRAFT

This kit contains all the equipment required to test from source the complete pitot & static air data system on the Dash 8-100/200/300/400 aircraft, as well as the means of pre-testing all adaptors and hoses prior to being fitted to the aircraft.

### **Pitot Test Adaptor**

#### **Part No. P22201-3 (2 req'd.)**

(Dash 8-100/200/300)

These units fit the pitot probes P/N

PH1100-1DH located on each side of the aircraft and when installed they will isolate and test each system separately or simultaneously, using pitot hose assembly supplied.

### **Pre-Test Probe**

#### **Part No. PT11882 (2 req'd.)**

(Dash 8-100/200/300)

When it becomes necessary to test the integrity of the pitot test adaptors and/or hoses and test set, these units are installed into the pitot test adaptors thus simulating the pitot head.

### **Static Test Adaptor**

#### **Part No. S51089-4 (1 req'd.)**

(Dash 8-100/200/300)

This unit fits the Captain's, F.O. and alternate static ports on the aircraft. This is a composite static vent.

N.B. Attach the hose to unit before installing on aircraft.

### **Static Blanking Adaptor**

#### **Part No. S51089B (1 req'd.)**

(Dash 8-100/200/300)

This unit is used in conjunction with the above mentioned test adaptor and is used to blank off the matching static vent on the opposite side of the aircraft. A test port is provided on the unit should it be desirable to check the integrity of the unit.

### **Static Pre-Test Plate**

#### **Part No. PT14097 (2 req'd.)**

(Dash 8-100/200/300)

These units are mounted onto the case cover and also act as storage pad. Before testing the integrity of the static test adaptors ensure that the mounting bolts are tight. The static testing and blanking adaptors may be tested separately or as a pair by connecting with the static hose assembly DH-7270CB.

### **Pitot & Dual Static Test Adaptor**

#### **Part No. PSS22202M-3-4-4 (2 req'd.)**

(Dash 8-400)

These units fit the pitot probes P/N C14135DA & C14135CA located on the nose and when installed they will isolate and test each system separately or simultaneously.

### **Pre-Test Probe**

#### **Part No. PT421-202M (2 req'd.)**

(Dash 8-400)

When it becomes necessary to test the integrity of the pitot & dual static test adaptors and/or hoses and test set, these units are installed into the adaptors thus simulating the pitot head.

April 14, 2009



**AIR DATA ACCESSORIES KIT  
MODEL No. DH8-834M  
DASH8-100/200/300/400 AIRCRAFT**

**Pitot Static Adaptor - Standby**

**Part No. PS22203M-3-4 (1 req'd.)**

(Dash 8-400)

This unit fits the pitot static probe, P/N C16193BA, located on the nose of the aircraft.

**Pre-Test Probe**

**Part No. PT421-203M (1 req'd.)**

(Dash 8-400)

When it becomes necessary to test the integrity of the pitot static test adaptor and/or hoses and test set, this unit is installed into the adaptor thus simulating the pitot head.

**Pitot Test Hose Assembly**

**Part No. DH-7270CB (1 req'd.)**

(Dash 8-100/200/300/400)

This hose is connected to each pitot inlet of the adaptors and is fitted with double acting quick disconnects for use when it is desirable to test only one pitot system. The connection for the pitot outlet of the pneumatic generator is included on this assembly.

**Static Test Hose Assembly**

**Part No. DH-5160CB (1 req'd.)**

(Dash 8-100/200/300/400)

This assembly attaches to the static fittings. The double acting quick disconnects operate in the same manner as that on the pitot test hose assembly. The extension fitting then connects to the static outlet hose of the pneumatic generator.

**Lubricating Fluid**

**Part No. LF5050 (1 req'd.)**

This fluid is used to lubricate the glands of the pitot & dual static and pitot static test adaptors. It is recommended that a small amount be used before installing adaptors on pitot head to ensure smooth installation onto the pitot probe.

**Seal Kit - Part No. SK201**

Two sets of spare seals for pitot test adaptors P/N P22201-3 are stowed in the case.

**Seal Kit - Part No. SK202M**

Two sets of spare seals for pitot & dual static test adaptors - P/N PSS22202M-3-4-4 are stowed in the case.

**Seal Kit - Part No. SK203M**

One set of spare seals for standby pitot static test adaptor - P/N PS22203M-3-4 is stowed in the case.

**Manual - Part No. 444-DH8-834**

One manual is supplied with each kit.

The equipment is enclosed in a case assembly - **Model No. 110XD-DH8-834.**