

PORTABLE ENGINE TEST SETS & TRIMMERS



To buy, sell, rent or trade-in this product please click on the link below:
<http://www.avionteq.com/Howell-Instruments-H337N-Engine-Test-Set-Analyzer.aspx>



H337N Series Engine Test Set

The H337N Series Engine Test Set is an advanced data collection and analysis system. It provides test cell equivalent analysis of engine performance while keeping the engine on-wing and the aircraft in service.

The H337N Series Test Set:

- Monitors engine temperature during engine operation
- Tests engine temperature indicator system
- Monitors engine RPM during engine operation
- Verifies accuracy of engine RPM system during engine operation
- Monitors exhaust pressure during engine operation
- Computes Engine Pressure Ratio (EPR)
- Measures fuel flow
- Measures vane angle
- Measures engine torque



Input Parameter Flexibility

Basic engine test parameters – temperature, speed and pressure – can all be scaled to the exact requirements of the engine being tested:

- Temperature can be displayed in °C or °F
- Engine speed can be scaled in %RPM, direct RPM, or in frequency (Hz)
- Externally measured pressure can be displayed inHg, ft-lbs or %Torque. Internally measured pressure can be displayed inHg or psi

A complete set of scale factors can be easily entered in to memory for up to ten different engine types. An alphanumeric display provides instructional prompts to the operator throughout the scaling procedure, and scaling information is retained permanently in memory unless changed by the operator. The Engine Select Switch allows the operator to select the specific calibration and scale factors appropriate for the engine under test.

Howell Instruments, Inc.
8945 South Freeway
Fort Worth, Texas 76140
www.howellinst.com
817-336-7411
Fax: 817-336-7874
info@howellinst.com

RE
BEFOR

PORTABLE ENGINE TEST SETS & TRIMMERS

H337N Series Engine Test Set

Cables and Accessories

Cables and other accessories are available for most airframe and engine applications. Dual engine test accessories are also available. Most cables supplied with earlier versions of the H337 can be used with the H337N.

Specifications			
Parameter	Range	Programmable Display Range	Accuracy
Engine Temperature (type K cr-al ¹ t/c)	0 to 1350 °C 0 to 2462 °F	0 to 1350 °C 0 to 2462 °F	±2 °C ±4 °F
Engine Temperature (TF30 cr-al ¹ curve)	0 to 1360 °C 0 to 2480 °F	0 to 1360 °C 0 to 2480 °F	±2 °C ±4 °F
Standard Day Temp	-60 to 100 °C Ambient	N/A	±4 °C @ 600 °C
Ambient Temperature	-60 to 100 °C (-76 to 212 °F)	-60 to 100 °C (-76 to 212 °F)	±0.3 °C ±0.5 °F
Frequency	10 to 30 KHz	30K counts max (%RPM, RPM, PPH, Hz)	±0.1 %
Internal Pressure Transducer	0 to 5 VDC	0 to 101.8 inHga	±0.25 inHga
Internal Pressure Transducer (cont'd)	0 to 5 VDC	0 to 50.00 psia	±0.12 psia
External Pressure Transducer (BH21717 Series)	0 to 6.200 VDC	9,999 counts max (inHg, psi, PCNT., ft-lb)	±0.2 %
Engine Pressure Ratio	0.800 to 3.500	N/A	±0.05
Resistance	0 to 40 ohms	N/A	±0.04 ohms
Insulation Resistance	0 to 200 Kohms	N/A	±2 Kohms
Temperature Indicator Calibration Signal	50 to 1000 °C	N/A	±2 °C
Power Requirements	115 VAC, 50 to 400 Hz, 230 VAC, 50 Hz, or 28 VDC		
Dimensions	7 inches H x 14 inches W x 14 inches D		
Weight	26.5 lbs (includes printer, excludes cables)		

¹Chromel[®] and Alumel[®] are registered trademarks of Hoskins Manufacturing Company.



Howell Instruments, Inc. • 8945 South Freeway • Fort Worth, Texas 76140
www.howellinst.com • 817-336-7411 • Fax: 817-336-7874 • info@howellinst.com

©2009 Howell Instruments, Inc.

PET337N