

To buy, sell, rent or trade-in this product please click on the link below:
www.avionteq.com/BriskHeat-ACR-4-D240KIT-Dual-Zone-Hot-bonder-kit



	ACR-3-D__KIT	ACR-4-DB__KIT
Display Size	8.4 in (213 mm)	10.1 in (256 mm)
Display Content	Displays 1 zone at a time	Displays both zones when both operational
TC Leads	30 gage wire x 6 ft long	24 gage wire x 6 ft long
Thermocouple Boxes	Built into Hot Bonder	Removeable with standard 15 foot CAT 5 Cable stored internally (replaceable)
Thermocouple Function	Control and/or alarm	Control and/or Alarm, or Monitor Only
Program/Recipe Storage	30 programs	Unlimited
Recipe Steps	3 ramp/soak steps, cooldown	Unlimited ramp/soak steps, with cooldown
Heat Source (Blanket Information)	No information recorded	Heating blanket information stored and resistance checks performed; data recorded
Sensor Type	Type-J (30 gage) with Mini Connector - 10 per zone	Type-J (24 gage) with Standard Connector - 10 per zone
Data Storage	Last 12 cures saved	Last 60 cures saved
Data Transfer	USB	USB
Realtime printing	1 per zone with replaceable ribbon	1 for both zones with thermal paper
Ethernet Connection (external)	None	Yes, for future expansion
Display Units of Measure	Degrees (°F, °C); Pressure (inHG, mmHG, mbar)	Degrees (°F, °C); Pressure (inHG, mmHG, kPa, mbar)
Vacuum Pump	(2) 28 inHG	(1) 29 inHG
Venturi Pump	(2) 28 inHG	(2) 28 inHG
Base Dimensions (dual)	22 x 18 x 10 in; 48 lbs (559 x 457 x 254 mm; 22 kg)	23 x 18 x 12 in; 46 lbs (584 x 457 x 305 mm; 21 kg)
Accessory Kit Dimensions (w/heaters)	19 x 15 x 7 in; 45 lbs (483 x 381 x 178 mm; 21 kg)	20 x 16 x 10 in; 48 lbs (508 x 406 x 254 mm; 22 kg)